



Q C *series*
shallow grooving tools



How to select parting and grooving tools

Structure of parting and grooving tools selection table

- Categorized as external machining, internal machining and profile machining.
- Concluded and separately listed according to product series (Little squirrel series and Supplementary series).

Dimensions

Application of external machining, internal machining and profile machining

External parting, grooving and turning tools

R-type shown

Type	Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench
		R	L	H x B	HF	LF	WF	CW			
QEAD	1212RA,07	▲	▲	12 x 12	12	125	12.15	1.5	7	ZDAD0100	
	1212RA,12	▲	▲	12 x 12	12	125	12.15	1.5	12	ZDAD0100	GB70-85-M4 x 12 WH40L
	1616RA,07	▲	▲	16 x 16	16	125	16.15	1.5	7	ZDAD0100	
	1616RA,12	▲	▲	16 x 16	16	125	16.15	1.5	12	ZDAD0100	
	2020RA,07	▲	▲	20 x 20	20	125	20.15	1.5	7	ZDAD0100	GB70-85-M5 x 16 WH40L
QEED	2020RA,12	▲	▲	20 x 20	20	125	20.15	1.5	12	ZDAD0100	
	1212RA,07	▲	▲	12 x 12	12	125	12.2	2	7	ZDEB0200	
	1212RA,10	▲	▲	12 x 12	12	125	12.2	2	10	ZDEB0200	GB70-85-M4 x 12 WH30L
	1212RA,14	▲	▲	12 x 12	12	125	12.2	2	14	ZDEB0200	
	1616RA,07	▲	▲	16 x 16	16	125	16.2	2	7	ZDEB0200	
	1616RA,10	▲	▲	16 x 16	16	125	16.2	2	10	ZDEB0200	
	1616RA,14	▲	▲	16 x 16	16	125	16.2	2	14	ZDEB0200	
	2020RA,07	▲	▲	20 x 20	20	125	20.2	2	7	ZDEB0200	GB70-85-M5 x 16 WH40L
	2020RA,10	▲	▲	20 x 20	20	125	20.2	2	10	ZDEB0200	
	2020RA,14	▲	▲	20 x 20	20	125	20.2	2	14	ZDEB0200	
QEFD	2525RA,07	▲	▲	25 x 25	25	160	25.2	2	7	ZDEB0200	
	2525RA,10	▲	▲	25 x 25	25	160	25.2	2	10	ZDEB0200	GB70-85-M6 x 20 WH50L
	2525RA,14	▲	▲	25 x 25	25	160	25.2	2	14	ZDEB0200	
	1616RA,10	▲	▲	16 x 16	16	125	16.25	2.5	10	ZQED0300	
	1616RA,17	▲	▲	16 x 16	16	125	16.25	2.5	17	ZQED0300	GB70-85-M5 x 20 WH40L
QEFD	2020RA,10	▲	▲	20 x 20	20	125	20.25	2.5	10	ZQED0300	
	2020RA,17	▲	▲	20 x 20	20	125	20.25	2.5	17	ZQED0300	GB70-85-M6 x 20 WH50L
	2525RA,10	▲	▲	25 x 25	25	160	25.25	2.5	10	ZQED0300	
	2525RA,17	▲	▲	25 x 25	25	160	25.25	2.5	17	ZQED0300	
	2525RA,19	▲	▲	25 x 25	25	160	25.3	2	19	ZQED0300	
QEFD	2020RA,17	▲	▲	20 x 20	20	125	20.3	3	17	ZQFD0400	
	2020RA,19	▲	▲	20 x 20	20	125	20.3	3	19	ZQFD0400	
	2525RA,10	▲	▲	25 x 25	25	160	25.3	3	10	ZQFD0400	GB70-85-M6 x 20 WH50L
QEFD	2525RA,17	▲	▲	25 x 25	25	160	25.3	3	17	ZQFD0400	
	2525RA,19	▲	▲	25 x 25	25	160	25.3	3	19	ZQFD0400	
	2525RA,22	▲	▲	25 x 25	25	160	25.4	4	22	ZQFD0400	GB70-85-M6 x 20 WH50L
	2525RA,19	▲	▲	25 x 25	25	160	25.3	4	19	ZQFD0400	

▲ Stock available △ Make-to-order

Specification of products

Including type, basic dimensions, applicable inserts and accessories.


Internal grooving and turning tools

R-type shown

Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
	R	L	DCON	LF	WF	CW	CDX _{max}	DMIN				
C20G-QEDR/L05-27	▲	▲	20	180	15.2	2.5	5	27	ZTED0250□□ ZRED0250□□	GB70-85-M4×12	WH30L	
C25R-QEDR/L07-33	▲	▲	25	200	20.3	2.5	7	33		GB70-85-M5×16	WH40L	
C32S-QEDR/L09-42	▲	▲	32	250	25.3	2.5	9	42		GB70-85-M5×20	WH40L	
C20G-QFDR/L05-27	▲	▲	20	180	15.2	3	5	27	ZTFD0300□□ ZRFD0300□□	GB70-85-M4×12	WH30L	
C25R-QFDR/L07-33	▲	▲	25	200	20.3	3	7	33		GB70-85-M5×16	WH40L	
C32S-QFDR/L09-42	▲	▲	32	250	25.3	3	9	42		GB70-85-M5×20	WH40L	
C25R-QQDR/L08-35	▲	▲	25	200	21.5	4	8	35	ZTQD0400□□ ZRDQ0400□□	GB70-85-M5×16	WH40L	
C32S-QQDR/L11-44	▲	▲	32	250	27.5	4	11	44		GB70-85-M6×20	WH50L	
C40T-QQDR/L13-54	▲	▲	40	300	33.5	4	13	54		GB70-85-M6×20	WH50L	
C25R-QHQR/L08-35	▲	▲	25	200	21.5	5	8	35	ZTHD0500□□ ZRH0500□□	GB70-85-M5×16	WH40L	
C32S-QHQR/L11-44	▲	▲	32	250	27.5	5	11	44		GB70-85-M6×20	WH50L	
C40T-QHQR/L13-54	▲	▲	40	300	33.5	5	13	54		GB70-85-M6×20	WH50L	
C25R-QKQR/L08-35	▲	▲	25	200	21.5	6	8	35	ZTKD0600□□ ZRKD0600□□	GB70-85-M5×16	WH40L	
C32S-QKQR/L11-44	▲	▲	32	250	27.5	6	11	44		GB70-85-M6×20	WH50L	
C40T-QKQR/L13-54	▲	▲	40	300	33.5	6	13	54		GB70-85-M6×20	WH50L	

▲ Stock available △ Make-to-order

Profile turning tools for Al



Type	Stock	R	L	DMIN (Minimum machining diameter)	Basic dimensions(mm)				Applicable inserts	Screw	Wrench
					DCON	WF	LF	CDX			
C40X-QLDR/L65-15A	▲	▲	160	40	21	320	65	ZRLD08-LH			
C40X-QLDR/L80-15A	▲	▲	160	40	21	320	80	ZRLD08-LH			
C40X-QKDR/L60-15A	▲	▲	160	40	20	320	60	ZRKD08-LH	GB70-85-M6 x 20		WH50L
C40X-QKDR/L75-15A	▲	▲	160	40	20	320	75	ZRKD08-LH			

▲ Stock available △ Make-to-order

Indicating the minimum machining diameter

The minimum machining diameter is very important for internal machining.



TURNING



Parting and grooving tools



Parting and grooving tools overview

A230-A232

Parting and grooving inserts

A233-A253

Introduction of G-series parting and grooving tools

A233-A234

Introduction of QC series shallow grooving tools

A235

Introduction of little squirrel series inserts chipbreaker

A236-A239

Parting, grooving and profiling inserts code key

A240

Inserts of little squirrel series

A241-A247

G-series parting and grooving inserts

A248-A249

QC series shallow grooving inserts code key

A250

QC series shallow grooving inserts

A251-A252

Inserts of ZQMX series

A253

Parting and grooving tools

A254-A282

Little squirrel series

Little squirrel series parting and grooving tools code key

A254-A255

External parting, grooving and turning tools

A256-A257

Precise grooving and turning tools

A257

External recess and profiling tools

A258

External grooving tools for difficult-to-machine materials

A258

External parting blade and holder for external parting

A259

End surface grooving and turning tools

A260-A265

L type tools for surface grooving and turning

A266-A267

Internal grooving and turning tools

A268

Profile turning tools for Al

A268

G-series parting and grooving tools

External parting, grooving and turning tools

A269

End surface grooving and turning tools

A270-A275

L type tools for surface grooving and turning

A276-A277

Internal grooving and turning tools

A278

QC series shallow grooving tools

QC series shallow grooving tools code key

A279

External shallow grooving tools

A280

Internal shallow grooving tools

A280

Supplementary series

Supplementary series parting and grooving tools code key

A281

QZQ external grooving series


A282



Application information for parting and grooving

A283-A284







Machining application	Machining type	Applicable tools	Corresponding inserts	Tool features and parameters
External machining	Parting	Little squirrel series QZ□□+QE□□  A259	Parting inserts ZP□S□□ 	- Assemble structure of parting blade and holder; good rigidity; adjustable parting range. - The maximum parting diameter is 120mm.
		Little squirrel series QE□□R/L  A256-A257	ZP□D□□  ZP□S□ 	- Inserts have three-dimensional chipbreaker with low cutting force and good performance on chip-breaking. - The maximum parting diameter is 60mm.
		Supplementary series QZQ□□R/L  A282	ZQMX□□ 	- Cutting edge strength is suitable for bad machining conditions. - The maximum parting diameter is 70mm.
		G-series GED□□R/L  A269	Parting inserts G□MD□□□□-GM 	- The special design of compression screw hole structure is adopted to realize high clamping force; the screw itself can form self-locking to ensure more reliable compression force. - High clamping stability to ensure the safety and stability of grooving and transverse turning. - Applicable for a variety of grooving and profiling inserts.
	Grooving and turning	Little squirrel series QE□□R/L  A256-A257	Double cutting edges for parting ZT□D□□  Profile turning ZR□D□□  Single cutting edge for deep grooving ZT□S□□ 	- A single tool with multiple applications such as grooving, parting and profile turning, reducing tools categories needed. - A multifunctional tool when used with grooving inserts. Suitable for profile machining. - The maximum slot depth machinable is 30mm.
		G-series GED□□R/L  A269	Parting inserts G□MD□□□□-GM 	- Reinforced grooving tools. - The special design of compression screw hole structure is adopted to realize high clamping force; the screw itself can form self-locking to ensure more reliable compression force. - High clamping stability to ensure the safety and stability of grooving and transverse turning. - Applicable for a variety of grooving and profiling inserts.

Machining application	Machining type	Applicable tools	Corresponding inserts	Tool features and parameters
External machining	Precise grooving	Little squirrel series QECD  A257 Little squirrel series QE□□R/L  A256-A257	Precise grooving ZT□□□□-EG  Edge width 1.2~2.4mm Precise grooving ZT□□□□-EG  Edge width 2.4~6.5mm	- Grinded insert used for precise grooving. - Edge width can be anything between 1.0-6.5mm, customized according to users' needs. - ZT□□□□-EG inserts: When edge width is between 1.2-2.4mm, the maximum cutting depth is 2.5mm. When edge width is above 2.4-6.5mm, the maximum cutting depth is 22mm.
	Shallow grooving	 QC series GQCR/L  A280	QC16/22□□□□ 	- Fine grinding of blades with high precision. - Sharp edges and high machining accuracy. - Three finely ground cutting edges for good economy. - For cutting shallow grooves, groove width 0.5-4.8mm. - Maximum depth of cut 4mm.
Internal machining	Grooving and turning	Little squirrel series C□□-Q□□R/L□  A268	Grooving, Turning ZT□□□□  Profile turning ZR□□□□ 	- By using inserts for grooving and profiling, one tool can be versatile, reducing the tool categories needed. - The maximum slot depth machinable is 13mm. - The minimum machining diameter is 27mm.
		G-series GID□□R/L  A278	Grooving inserts G□MD□□□□-GM 	- The minimum machining diameter is 20mm. - Maximum depth of cut 11mm. - Applicable for a variety of grooving and profiling inserts.
	Shallow grooving	QC series □□□□-QC□□R/L□  A280	QC11/16/22□□□□ 	- Fine grinding of blades with high precision. - Machining groove width 0.5-4.8mm. - Minimum machining diameter 16mm. - Maximum depth of cut 4mm.



Parting and grooving tools overview

Machining application	Machining type	Applicable tools	Corresponding inserts	Tool features and parameters
End surface machining	Grooving and turning	G-series GFDR/L  A274-A275	Grooving inserts GMDD-GM 	- Achieve end face machining with a diameter of 28mm. - The insert positioning structure is scientifically designed, and the first cutting range is reasonably planned to ensure that the tool body has high strength. - High-strength cutter body rounded face for more precise tool selection. - Grooving diameter range 28-600mm. - Applicable for a variety of grooving and profiling inserts.
		Little squirrel series QFHH  A262-A265	Grooving, Turning ZTH  Profile turning ZTH 	- By using inserts for grooving and profiling, one tool can be versatile, reducing the tool categories needed. - Grooving diameter is 48-400mm. - Grooving depth is 10-30mm.
		Little squirrel series QFHL  A266-A267	Grooving, Turning ZTH  Profile turning ZTH 	90° holder, top clamping. - By using inserts for grooving and profiling, one tool can be versatile, reducing the tool categories needed. - Grooving diameter is 48~400mm. - Grooving depth is 10~30mm.
Recess machining	Recess machining	Little squirrel series QXHH  A258	Grooving, Turning ZTH  Profile turning ZTH 	- The unique tool for recess machining. - Complete range of specifications, able to achieve various recess machining.
AI profiling	Inner wall and surface machining	Little squirrel series C40X  A268	Little squirrel series ZTH-LH 	- The unique tool for profiling of AI material. - Cutting edge is designed to combine sharpness and strength, suitable for continuous and intermittent turning. - Used for external, surface and inner wall machining of AI wheel hub.
Tools for aviation and aerospace industries	External machining	Little squirrel series QESH  A258	Little squirrel series ZIG  Little squirrel series ZIMF 	- V-type locating, top clamping, precise locating, safe clamping. - Normal square-ended inserts and precise square-ended inserts are suitable for adhesive materials hard to machine such as Ni-base high-temperature alloy, Ti alloy and stainless steel, etc.
	Non-standard Tools	Non-standard tools to match workpiece 	Select and manufacture as required	Tailor made solutions for machining various parts to satisfy your requirements.

G-series

high-efficiency parting & grooving inserts

Better clamping stability:

- The new inserts clamping design achieves higher clamping force and better processing;
- Anti-vibration design, excellent surface finish.

High precision inserts:

Edge width 2-4mm, the tolerance of edge width reach $\pm 0.03\text{mm}$;
Edge width 5-6mm, the tolerance of edge width reach $\pm 0.04\text{mm}$;
High consistency of inserts, realizing high-precision machining.

Strengthen the pressing position of the toolholder to ensure the clamping force of the inserts



Reinforced structure design of cutter body position



The minimum cutting diameter of the end face can reach $\phi 28\text{mm}$



The minimum processing diameter of the inner hole can reach $\phi 20\text{mm}$

*GIMD / GRMD type inserts can't be installed on little squirrel series parting and grooving holders.

Good chip treatment -GM chipbreaker

Bevel design:

Control chip curled upward and removal.


Raised top:

Ensure the chips curled and broken during processing and inhibit the generation of built-up edge.



The variable rake angle design of the rake face ensures the sharpness and strength of the insert edge.

Curved cutting edge structure design, self-centering processing, can meet various processing conditions such as low and high feed, continuous and intermittent etc., strong versatility.



G-series



Supercrystalline Nano Coating

YB9120

Add tough alloy elements to TiAlN coating to obtain high toughness TiAlN-based ceramic coating; Achieve synergistic improvement of coating wear resistance, toughness and high-temperature service performance, grooving and parting PVD coating grades, can meet the processing requirements of P, M, K materials such as parting, grooving, profiling, etc., to achieve long life and safety efficient processing.



YBC103

A new generation of CVD-coated grades, comprehensively improved the performance of insert edge strength, wear resistance and high temperature oxidation resistance, suitable for efficient processing of various steel materials.

Application case

● Chip curled stably:


Machined material: Stainless steel/45#
Cutting parameters: $V_c = 150\text{m/min}$, $f = 0.15\text{mm/r}$
Inserts: GTMD304-GM/YB9120



Under the same working conditions, our company's GTMD series grooving inserts have better chip breaking performance, which can reduce the downtime for chip removal.

● Excellent performance on machining:

Machined material: Cast iron
Cutting parameters: $V_c = 180\text{m/min}$, $f = 0.15\text{mm/r}$
Inserts: GTMD304-GM/YBC103



Under the same working conditions, our company's GTMD series inserts have better wear resistance, tool life is longer.

Little squirrel series




QC series shallow grooving tools

**Machine industry shallow
groove processing tool**


Widely used for shallow groove machining
of shaft and ring parts in machinery industry


 Shallow groove series tool grooving
range

Groove depth(mm)



Groove depth(mm)





Little-Squirrel Series

Profile turning inserts for parting of aviation titanium alloy, super alloy

-NF

Single-headed precision profile turning inserts

Sharp edge, small cutting force, good surface quality;
Indexing accuracy reaches $\pm 0.025\text{mm}$, safe and stable clamping;
Mainly applied in finishing of super alloy, titanium alloy.

-NM

Precision profile turning inserts

Sharp edge, small cutting force, good surface quality;
Indexing accuracy reaches $\pm 0.025\text{mm}$;
Highly economical, two edges available;
Compatible with little squirrel tool holder, suitable for small depth profile finishing and semi-finishing of super alloy and titanium alloy.



-SM

Single-headed groove turning inserts

Straight edge, excellent surface quality;

Sharp edge, smaller cutting force;

Good chip breaking;

Mainly used for rough machining of super alloy and titanium alloy.



-MM

Straight edge groove turning inserts

High edge strength, sharp edge;

Highly economical, two edges available, compatible with little squirrel tool holder;

With special grades, suitable for roughing with small cutting depths of super alloy and titanium alloy.



Case

Insert: YBG105/ZIMF604N-SM

Hardness of workpiece material: GH4169(HB380)

Cutting data: $V_c=45\text{m/min}$, $f=0.2\text{mm/r}$

Coolant: Water



Products of company A



YBG105/ZIMF604N-SM

Conclusion: Under the same conditions, chip breaking performance is better and the stop time to remove long winding chips is reduced.


-MG Chipbreaker

Customized -MG chipbreaker series

Suitable for parting, grooving, profile turning and turning, etc. Easy machining and unobstructed chip flow lead to improved surface quality.

Human-centered design realizes various application of one single insert, reducing number of tools needed

The insert with same edge width can fit on corresponding tool holders to satisfy the requirements of external, internal and end face grooving or turning by using minimum numbers of inserts and tool holders, effectively reducing cost of tool storage and management.



The cutting force is reduced by 20%, and the vibration is diminished.

Unique and professional structure design of parting inserts

- A special flank structure is designed to reduce cutting resistant force by 20% and diminish vibration, which improves the surface quality.
- A special edge design requires less rigidity of machine. It can be used on low power machines.



Little squirrel series

-EG


Precision grooving and profile turning inserts

Special chipbreaker design, suitable for precise grooving of low-carbon steel, stainless steel, adhesive materials and non-ferrous metal.

The tolerance of the edge width CW of precise grooving and profiling inserts can reach ± 0.025 . Inserts can also be mounted on the corresponding specifications of original tool series.

-EG Precision grooving inserts

The edge width can be anything between **1.0-6.5mm** according to your requirements.



The width of the Little Squirrel series precise grooving inserts can be anything between 1.0mm to 6.5mm, which means products with any edge width or nose radius can be provided according to customers' requirements. The inserts are mainly used for precise grooving, such as sealing slot and locating slot, etc.

-EG Precision profile turning inserts




The Little Squirrel series precise profiling and turning inserts are mainly used for precise grooving and profiling.

-LC/-LH

Profile turning inserts for Al

The special chipbreaker for aluminum profiling is designed to combine sharpness and strength of the cutting edge, effectively reducing the friction between chips and the rake face. The inserts are suitable for continuous and intermittent profiling of Al alloy.



Suitable for various machining of Al wheel boss periphery, surface and inner wall, etc.



Little squirrel series parting, grooving and profiling inserts code key

General turning

Parting and grooving

Little squirrel series parting and grooving inserts

Insert applications

ZP > Parting **ZT** > Grooving and turning
ZR > Profiling

Code of locating slot

Code of locating slot	A	B	E	F	G	H	K	L
Corresponding edge width of inserts	1.5	2.0	2.5	3.0	4.0	5.0	6.0	8.0

Code of cutting edge number

S > Single cutting edge **D** > Double cutting edge

ZP G D 04 04 - M G

Cutting edge width



015=1.5mm
02=2.0mm
025=2.5mm
03=3.0mm
04=4.0mm
05=5.0mm
06=6.0mm
08=8.0mm

Nose radius



02=0.2mm
03=0.3mm
04=0.4mm
08=0.8mm


Tolerance class

M > M-level tolerance
E > E-level tolerance

Chipbreaker code

G > Curve edges universal chipbreaker, suitable for machining various materials
M > linear edges universal chipbreaker, suitable for machining various materials
F > Special chipbreaker

Parting inserts



Type		Basic dimensions(mm)			Grade				
					CVD Coating		PVD Coating		Cemented carbide
		CW ^{+0.1} ₀	RE±0.1	Cutting depth CDX _{max}	YBC151	YBC251	YBG202	YBG302	YD101
Double edges	ZPAD01502-MG	1.5	0.2	12		○	★	○	
	ZPBD0202-MG	2.0	0.2	14		○	★	○	
	ZPED02502-MG	2.5	0.2	17		○	★	★	
	ZPFD0302-MG	3.0	0.2	17		○	★	○	
	ZPGD0402-MG	4.0	0.2	22		○	★	○	
	ZPHD0503-MG	5.0	0.3	22		○	★	○	
	ZPKD0604-MG	6.0	0.4	22		○	★	○	
Single edge	ZPES02502-MG	2.5	0.2			○	★	★	
	ZPFS0302-MG	3.0	0.2			○	★	○	
	ZPGS0402-MG	4.0	0.2			○	★	○	
	ZPHS0503-MG	5.0	0.3			○	★	○	
	ZPKS0604-MG	6.0	0.4			○	★	○	

Single edge tool for cutter plate only

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order


Please reduce the feed speed by 30% when the insert is approaching the centre of workpiece. This can prolong tool life.

Optimal chipbreaker structure can control chip flow and curling well.

Cutting resistant force is reduced by 20% and vibration is diminished.



Grooving and turning inserts



Type	Basic dimensions(mm)			Grade					
				CVD Coating		PVD Coating			Cemented carbide
	$CW^{+0.1}_0$	$RE_{\pm 0.1}$	Cutting depth CDX_{max}	YBC151	YBC251	YBG202	YBG205	YBG302	YD101
Double edges	ZTED02503-MG	2.5	0.3	17	○	○	●	★	★
	ZTFD0303-MG	3.0	0.3	17	○	○	●	★	★
	ZTGD0404-MG	4.0	0.4	22	●	○	●	★	★
	ZTHD0504-MG	5.0	0.4	22		○	●	★	★
	ZTKD0608-MG	6.0	0.8	22		○	●	★	★
Single edge	ZTHS0504-MG	5.0	0.4		○	○	★	○	
	ZTKS0608-MG	6.0	0.8		○	○	★	○	

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order




Type	Basic dimensions(mm)			Grade					
				CVD Coating		PVD Coating			Cemented carbide
	CW	$RE_{\pm 0.1}$	Cutting depth CDX_{max}	YBC151	YBC251	YBG202	YBG205	YBG302	YD101
Double edges	ZTAD01502-MM	1.5±0.03	0.2	12	○	○	●	★	○
	ZTBD02002-MM	2.0±0.03	0.2	14	○	○	●	★	○
	ZTED02503-MM	2.5±0.03	0.3	17	○	○	●	★	○
	ZTFD0303-MM	3.0±0.03	0.3	17	○	○	●	★	○
	ZTGD0404-MM	4.0±0.04	0.4	22	○	○	●	★	○
	ZTHD0504-MM	5.0±0.04	0.4	22	○	○	●	★	○
	ZTKD0608-MM	6.0±0.04	0.8	22	○	○	●	★	○
	ZTLD0808-MM	8.0±0.05	0.8	28	○	○	●	★	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order


Precise grooving and turning inserts



1.0~2.4mm series



>2.4~6.5mm series



Type		Type			Grade					
					CVD Coating		PVD Coating			Cemented carbide
		CW ± 0.025	RE ⁽²⁾ ± 0.05	Cutting depth CDX _{max}	YBC151	YBC251	YBG202	YBG205	YBG302	YD101
Double edges	ZTCD□□□□□ ⁽¹⁾ -EG	1.0~1.6	See note. (2)	2.6	○	○	○	★	○	
		1.6~2.4		3.4						
	ZTED□□□□□-EG	2.4~3.0		17	○	○	○	★	○	
	ZTFD□□□□□-EG	3.0~3.8		17	○	○	○	★	○	
	ZTGD□□□□□-EG	3.8~4.8		22	○	○	○	★	○	
	ZTHD□□□□□-EG	4.8~5.8		22	○	○	○	★	○	
	ZTKD□□□□□-EG	5.8~6.5		22	○	○	○	★	○	

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order

Note: (1) □ The code here in the description is determined by edge width and nose radius requested by customers. For example, when the customer requires an edge width of 3.5mm and a nose radius of 0.3mm, the description of the insert would be ZTFD03503-EG.

(2) The nose radius range is $0.2 \leq R \leq 0.5$ on request.


General turning

Parting and grooving

Little squirrel series parting and grooving inserts




Single-head grooving and turning inserts for semi-finishing and roughing difficult-to-machine materials



Type	Basic dimensions(mm)				Grade				
					PVD Coating				Cemented carbide
	CW±0.05	RE±0.1	W1	INSL	YBG102	YBG202	YBG205	YBS103	YD101
ZIMF304N-NM	3	0.4	2.4	15.3	★	○	★	●	○
ZIMF406N-NM	4	0.6	3.2	15.3	★	○	★	●	○
ZIMF506N-NM	5	0.6	4.0	15.3	★	○	★	○	○
ZIMF608N-NM	6	0.8	4.0	15.3	★	○	★	○	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order


Single-head grooving and turning inserts for semi-finishing and roughing difficult-to-machine materials



Type	Basic dimensions(mm)				Grade				
					PVD Coating				Cemented carbide
	CW±0.05	RE±0.1	W1	INSL	YBG105	YBG212	YBG205	YBS103	YD101
ZIMF304N-SM	3	0.4	2.4	15.3	★	★		●	○
ZIMF404N-SM	4	0.4	3.2	15.3	★	★		○	○
ZIMF504N-SM	5	0.4	4.0	15.3	★	★		○	○
ZIMF604N-SM	6	0.4	5.1	15.3	★	★		○	○

★Recommended grade (always stock available) ●Available grade (always stock available) ○Make-to-order


Profiling inserts



Type		Basic dimensions(mm)		Grade					
				CVD Coating		PVD Coating			Cemented carbide
		CW ^{+0.1} ₀	Cutting depth CDX _{max}	YBC151	YBC251	YBG202	YBG205	YBG302	YD101
Double edges	ZRED025-MG	2.5	17.5		○	●	★	★	
	ZRFD03-MG	3.0	17		○	●	★	★	
	ZRGD04-MG	4.0	21		○	●	★	★	
	ZRHD05-MG	5.0	20		○	○	★	★	
	ZRKD06-MG	6.0	19		○	●	★	★	

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order


Profiling inserts



Type		Basic dimensions(mm)		Grade						
				CVD Coating		PVD Coating				Cemented carbide
		CW ^{+0.25} ₀	Cutting depth CDX _{max}	YBC151	YBC251	YBG105	YBG212	YBG302	YBS103	YD101
Double edges	ZRFD03-NM	3	17			★	★		●	
	ZRGD04-NM	4	21			★	★		●	
	ZRHD05-NM	5	20			★	★		○	
	ZRKD06-NM	6	19			★	★		○	

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order

Precision profiling inserts




Type		Basic dimensions(mm)		Grade				
				CVD Coating		PVD Coating		Cemented carbide
		CW ± 0.025	Cutting depth CDX _{max}	YBC151	YBC251	YBG202	YBG302	YD101
Double edges	ZRFD03- EG	3.0	17		○		○	
	ZRGD04- EG	4.0	21		○		○	
	ZRHD05-EG	5.0	20		○		○	
	ZRKD06-EG	6.0	19		○		○	

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order




Single-head inserts for profiling difficult-to-machine materials



Type	Basic dimensions(mm)			Grade			
				PVD Coating			Cemented carbide
	CW ± 0.025	W1	INSL	YBG102	YBG202	YBS103	YD101
ZIGQ3N-NM	3	2.4	15.3	★	○	●	○
ZIGQ4N-NM	4	3.2	15.3	★	○	●	○
ZIGQ5N-NM	5	4.0	15.3	★	○	○	○
ZIGQ6N-NM	6	5.0	15.3	★	○	○	○

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order


Single-head inserts for profiling difficult-to-machine materials



Type	Basic dimensions(mm)			Grade			
				PVD Coating			Cemented carbide
	CW ± 0.025	W1	INSL	YBG105	YBG212	YBS103	YD101
ZIGQ3N-NF	3	2.4	15.3	★	★	●	
ZIGQ4N-NF	4	3.2	15.3	★	★	○	
ZIGQ5N-NF	5	4.0	15.3	★	★	○	
ZIGQ6N-NF	6	5.0	15.3	★	★	○	

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order

Profiling inserts for AI



Type	Basic dimensions(mm)		Grade
			Cemented carbide
	CW ± 0.02	Cutting depth CDX _{max}	YD101
ZRKD06-LH	6.0	19	★
ZRLD08-LH	8.0	22	★


★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order

General turning

Parting and grooving

Little squirrel series parting and grooving inserts

Profiling inserts for AI




Type	Basic dimensions(mm)			Grade
				Cemented carbide
	CW ± 0.02	RE	Cutting depth CDX _{max}	YD101
ZILD08-LC	8.0	4.0	22	●

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order



Grooving and turning inserts




Type	Basic dimensions(mm)					Grade	
						CVD Coating	PVD Coating
	CW	W1	INSL	CDX	RE	YBC103	YB9120
GTMD2502-GM	2.5	2	17	14	0.2	●	●
GTMD302-GM	3.0	2.3	17	14	0.2	●	●
GTMD304-GM	3.0	2.3	17	14	0.4	●	●
GTMD402-GM	4.0	3.2	20	17	0.2	●	●
GTMD404-GM	4.0	3.2	20	17	0.4	●	●
GTMD504-GM	5.0	4.2	20	17	0.4	●	●
GTMD508-GM	5.0	4.2	20	17	0.8	●	●
GTMD604-GM	6.0	5.2	20	17	0.4	●	●
GTMD608-GM	6.0	5.2	20	17	0.8	●	●


★ Recommended grade (always stock available)

● Available grade (always stock available)

○ Make-to-order



Profiling inserts



Type	Basic dimensions(mm)					Grade	
						CVD Coating	PVD Coating
	CW	W1	INSL	CDX	RE	YBC103	YB9120
GRMD315-GM	3.0	2.3	17	14	1.5	●	●
GRMD420-GM	4.0	3.2	20	17	2.0	●	●
GRMD525-GM	5.0	4.2	20	17	2.5	●	●
GRMD630-GM	6.0	5.2	20	17	3.0	●	●


★Recommended grade (always stock available)

●Available grade (always stock available)

○Make-to-order

General
turningParting and
grooving

G-series parting and grooving inserts





QC series

shallow grooving inserts code key

● Square head shallow grooving inserts

QCShallow grooving
inserts**22**Cutting edge length
code

11

16

22

Inner tangent circle
diameter(mm)

6.35

9.525

12.70

R**300**

Grooving width(mm)

Code

Width

050

0.50

100

1.00

...

...

480

4.80

R**03**Rounding or
chamfering(mm)

Code

Size

02

0.2

03

0.3

04

0.4

Direction

Code

Form

R

Rightward



L

Leftward



Inserts tip form

Code

Form

R

Circular arc



C

Chamfering



● Round head shallow grooving inserts

QCShallow grooving
inserts**22**Cutting edge length
code

11

16

22

Inner tangent circle
diameter(mm)

6.35

9.525

12.70

R

Direction

R

Rightward



L

Leftward

**300**

Grooving width(mm)

Code

Width

050

0.50

100

1.00

...

...

480


4.80

RHead form:
round head

Square head shallow grooving inserts



R-type shown

General
turningParting and
grooving

QC series shallow grooving inserts

Type		Basic dimensions(mm)						Grade	
								PVD Coating	
		S±0.025	LA	RE	IC	S1	D1	YBG202	YBG205
QC11R/L	120-R02	1.20	1.50	0.2	6.35	3.18	2.8	○	○
	125-R02	1.25	1.50	0.2	6.35	3.18	2.8	○	○
	145-R02	1.45	1.50	0.2	6.35	3.18	2.8	○	○
	150-R02	1.50	1.50	0.2	6.35	3.18	2.8	○	○
	200-R02	2.00	2.00	0.2	6.35	3.18	2.8	○	○
	225-R02	2.25	2.00	0.2	6.35	3.18	2.8	○	○
QC16R/L	110-R01	1.10	2.00	0.1	9.525	3.18	4.4	○	○
	125-R02	1.25	2.00	0.2	9.525	3.18	4.4	○	○
	145-R02	1.45	2.00	0.2	9.525	3.18	4.4	○	○
	150-R02	1.50	2.00	0.2	9.525	3.18	4.4	○	★
	175-R02	1.75	2.00	0.2	9.525	3.18	4.4	○	○
	185-R02	1.85	2.50	0.2	9.525	3.18	4.4	○	○
	200-R02	2.00	2.50	0.2	9.525	3.18	4.4	○	★
	250-R02	2.50	2.50	0.2	9.525	3.18	4.4	○	★
	300-R02	3.00	3.00	0.2	9.525	3.18	4.4	○	★
QC22R/L	125-R02	1.25	2.00	0.2	12.70	4.76	5.5	○	○
	145-R02	1.45	2.00	0.2	12.70	4.76	5.5	○	○
	150-R02	1.50	3.50	0.2	12.70	4.76	5.5	○	★
	175-R02	1.75	3.50	0.2	12.70	4.76	5.5	○	○
	185-R02	1.85	3.50	0.2	12.70	4.76	5.5	○	○
	200-R02	2.00	3.50	0.2	12.70	4.76	5.5	○	★
	230-R02	2.30	3.50	0.2	12.70	4.76	5.5	○	○
	250-R03	2.50	4.00	0.3	12.70	4.76	5.5	○	★
	265-R03	2.65	4.00	0.3	12.70	4.76	5.5	○	○
	280-R03	2.80	4.00	0.3	12.70	4.76	5.5	○	○

★Recommended grade (always stock available)

●Available grade (always stock available)


○Make-to-order



Square head shallow grooving inserts



R-type shown



Type		Basic dimensions(mm)						Grade	
								PVD Coating	
		S ± 0.025	LA	RE	IC	S1	D1	YBG202	YBG205
QC22R/L	300-R03	3.00	4.00	0.3	12.70	4.76	5.5	○	★
	320-R03	3.20	4.00	0.3	12.70	4.76	5.5	○	○
	330-R03	3.30	4.00	0.3	12.70	4.76	5.5	○	○
	350-R03	3.50	5.00	0.3	12.70	4.76	5.5	○	★
	400-R04	4.00	5.00	0.4	12.70	4.76	5.5	○	★
	430-R04	4.30	5.00	0.4	12.70	4.76	5.5	○	○
	450-R04	4.50	5.00	0.4	12.70	4.76	5.5	○	○
	480-R04	4.80	5.00	0.4	12.70	5.06	5.5	○	○

★ Recommended grade (always stock available)

● Available grade (always stock available)

○ Make-to-order

Example of special specification customization:


1. Custom-made insert width of 1.6mm, the tip form of the arc form, arc radius of 0.3mm right blade, IC value of 12.7mm, then the custom-made insert model is QC22R160-R03.

2. Customized edge width range: QC11: 0.50~3.0mm; QC16: 0.50~3.0mm; QC22: 1.0~4.8mm.

Round head shallow grooving inserts



R-type shown



Type		Basic dimensions(mm)						Grade	
								PVD Coating	
		S ± 0.025	LA	RE	IC	S1	D1	YBG202	YBG205
QC16R/L	200R	2.00	2.50	1.00	12.70	3.18	4.4	○	○
	300R	3.00	2.50	1.50	12.70	3.18	4.4	○	○
QC22R/L	100R	1.00	2.00	0.50	12.70	4.76	5.5	○	○
	150R	1.50	3.50	0.75	12.70	4.76	5.5	○	○
	200R	2.00	3.50	1.00	12.70	4.76	5.5	○	○
	250R	2.50	4.00	1.25	12.70	4.76	5.5	○	○
	300R	3.00	4.00	1.50	12.70	4.76	5.5	○	○
	400R	4.00	5.00	2.00	12.70	4.76	5.5	○	○

★ Recommended grade (always stock available)


● Available grade (always stock available)

○ Make-to-order

Example of special specification customization:


Custom-made inserts width of 1.6mm, the tip form of the arc form, the arc radius of 0.8mm right insert, then the custom-made insert model is QC22R160R.

ZQMX series



Type	Basic dimensions(mm)				Grade		
					CVD Coating	Cemented carbide	
	PDPT	CW	RE	INSL	YBC251	YC40	YD201
ZQMX3N11-1E	4.4	3.125	0.3	11	●	●	●
ZQMX4N11-1E	4.95	4.125	0.3	11	●	●	●
ZQMX5N11-1E	5.0	5.125	0.3	11	●	●	●
ZQMX6N11-1E	5.28	6.4	0.3	11	●	●	○

★ Recommended grade (always stock available) ● Available grade (always stock available) ○ Make-to-order



General turning

Parting and grooving

Supplementary series parting and grooving inserts



TURNING

Parting and grooving tools

Little squirrel series parting and grooving tools

Little squirrel series parting and grooving tools code key

● External and surface turning

General turning

Parting and grooving

Little squirrel series parting and grooving tools

Code of grooving tools

Machining mode

E > External cutting **F** > End surface cutting

Code of locating slot

Accords with locating slot code of insert and corresponds to certain range of insert edge width

Code of edge number of corresponding inserts

S > Single cutting edge **D** > Double cutting edge

Q E G D - **2525 R S**
32 N

Q F G D 2525 R 22 S - 130 H

Nose height and width of tool holder

Left and right hand of tool

R > Right **L** > Left **N** > Both are acceptable

Maximum cutting depth

Supplementary code


S: Strengthened tool holder for external and surface deep grooving

The minimum diameter of end surface grooving tools for initial machining


Holder type of end surface grooving tools

H > Straight holder **L** > 90° holder

● Holder for parting blade




● Internal machining






External parting, grooving and turning tools



R-type shown




Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}			
QEAD	1212R/L07	▲	▲	12×12	12	125	12.15	1.5	7	ZQAD015□□	GB70-85-M4×12	WH30L
	1212R/L12	▲	▲	12×12	12	125	12.15	1.5	12	ZQAD015□□		
	1616R/L07	▲	▲	16×16	16	125	16.15	1.5	7	ZQAD015□□	GB70-85-M5×16	WH40L
	1616R/L12	▲	▲	16×16	16	125	16.15	1.5	12	ZQAD015□□		
	2020R/L07	▲	▲	20×20	20	125	20.15	1.5	7	ZQAD015□□		
	2020R/L12	▲	▲	20×20	20	125	20.15	1.5	12	ZQAD015□□		
QEBD	1212R/L07	▲	▲	12×12	12	125	12.2	2	7	ZQBD02□□	GB70-85-M4×12	WH30L
	1212R/L10	▲	▲	12×12	12	125	12.2	2	10	ZQBD02□□		
	1212R/L14	▲	▲	12×12	12	125	12.2	2	14	ZQBD02□□	GB70-85-M5×16	WH40L
	1616R/L07	▲	▲	16×16	16	125	16.2	2	7	ZQBD02□□		
	1616R/L10	▲	▲	16×16	16	125	16.2	2	10	ZQBD02□□		
	1616R/L14	▲	▲	16×16	16	125	16.2	2	14	ZQBD02□□		
	2020R/L07	▲	▲	20×20	20	125	20.2	2	7	ZQBD02□□		
	2020R/L10	▲	▲	20×20	20	125	20.2	2	10	ZQBD02□□		
	2020R/L14	▲	▲	20×20	20	125	20.2	2	14	ZQBD02□□		
	2525R/L07	▲	▲	25×25	25	150	25.2	2	7	ZQBD02□□	GB70-85-M6×20	WH50L
	2525R/L10	▲	▲	25×25	25	150	25.2	2	10	ZQBD02□□		
	2525R/L14	▲	▲	25×25	25	150	25.2	2	14	ZQBD02□□		
QEED	1616R/L10	▲	▲	16×16	16	125	16.25	2.5	10	ZQED025□□	GB70-85-M5×20	WH40L
	1616R/L17	▲	▲	16×16	16	125	16.25	2.5	17	ZQED025□□		
	2020R/L10	▲	▲	20×20	20	125	20.25	2.5	10	ZQED025□□	GB70-85-M6×20	WH50L
	2020R/L17	▲	▲	20×20	20	125	20.25	2.5	17	ZQED025□□		
	2525R/L10	▲	▲	25×25	25	150	25.25	2.5	10	ZQED025□□		
	2525R/L17	▲	▲	25×25	25	150	25.25	2.5	17	ZQED025□□		
QEFD	1616R/L10	▲	▲	16×16	16	125	16.3	3	10	ZQFD03□□	GB70-85-M5×20	WH40L
	1616R/L17	▲	▲	16×16	16	125	16.3	3	17	ZQFD03□□		
	2020R/L10	▲	▲	20×20	20	125	20.3	3	10	ZQFD03□□	GB70-85-M6×20	WH50L
	2020R/L17	▲	▲	20×20	20	125	20.3	3	17	ZQFD03□□		
	2525R/L10	▲	▲	25×25	25	150	25.3	3	10	ZQFD03□□		
	2525R/L17	▲	▲	25×25	25	150	25.3	3	17	ZQFD03□□		
QEGD	2020R/L13	▲	▲	20×20	20	140	20.5	4	13	ZQGD04□□	GB70-85-M6×20	WH50L
	2020R/L22	▲	▲	20×20	20	140	20.5	4	22	ZQGD04□□		
	2525R/L13	▲	▲	25×25	25	150	25.5	4	13	ZQGD04□□		


▲Stock available

△Make-to-order

External parting, grooving and turning tools



R-type shown




Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}			
QEGD	2525R/L22	▲	▲	25×25	25	150	25.5	4	22	Z□GD04□□	GB70-85-M6×20	WH50L
	3232R/L13	▲	▲	32×32	32	170	32.5	4	13	Z□GD04□□		
	3232R/L22	▲	▲	32×32	32	170	32.5	4	22	Z□GD04□□		
QEHD	2525R/L13	▲	▲	25×25	25	150	25.5	5	13	Z□HD05□□	GB70-85-M6×20	WH50L
	2525R/L22	▲	▲	25×25	25	150	25.5	5	22	Z□HD05□□		
QEHS	2525N30	▲	▲	25×25	25	150	15	5	30	Z□HS05□□		
QEHD	3232R/L13	▲	▲	32×32	32	170	32.5	5	13	Z□HD05□□		
	3232R/L22	▲	▲	32×32	32	170	32.5	5	22	Z□HD05□□		
QEHS	3232N30	▲	▲	32×32	32	170	18.5	5	30	Z□HS05□□		
QEKD	2525R/L13	▲	▲	25×25	25	150	25.6	6	13	Z□KD06□□	GB70-85-M6×20	WH50L
	2525R/L22	▲	▲	25×25	25	150	25.6	6	22	Z□KD06□□		
QEKS	2525N30	▲	▲	25×25	25	150	15.5	6	30	Z□KS06□□		
QEKD	3232R/L13	▲	▲	32×32	32	170	32.6	6	13	Z□KD06□□		
	3232R/L22	▲	▲	32×32	32	170	32.6	6	22	Z□KD06□□		
QEKS	3232N30	▲	▲	32×32	32	170	19	6	30	Z□KS06□□		
QELD	2525R/L16	▲	▲	25×25	25	150	26	8	16	ZTLD0808-MM	GB70-85-M6×20	WH50L
	2525R/L25	▲	▲	25×25	25	150	26	8	25	ZTLD0808-MM	GB70-85-M6×20	WH50L
	3232R/L28	▲	▲	32×32	32	170	33	8	28	ZTLD0808-MM	GB70-85-M8×30	WH60L



▲Stock available

△Make-to-order

Precision grooving and turning tools



R-type shown



Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}			
QECD	1616R/L025	△	△	16×16	26	125	14.75	1.0~2.4	2.5	ZTCD□□□□□□-EG	GB70-85-M5×20	WH40L
	2020R/L025	▲	△	20×20	20	125	18.75				GB70-85-M6×20	WH50L
	2525R/L025	▲	△	25×25	25	150	23.75					

▲Stock available

△Make-to-order


General turning

Parting and grooving


Little squirrel series parting and grooving tools



External recess and profiling tools




R-type shown




Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}			
QXFD	2020R/L03-45	△	△	20×20	20	125	23	3.0	3.0	ZR(T)FD03-□□	GB70-85-M6×20	WH50L
	2525R/L03-45	△	△	25×25	25	150	28					
	3232R/L03-45	△	△	32×32	32	170	35					
QXGD	2020R/L03-45	△	△	20×20	20	125	23	4.0	3.0	ZR(T)GD04-□□		
	2525R/L03-45	△	△	25×25	25	150	28					
	3232R/L03-45	△	△	32×32	32	170	35					
QXHD	2020R/L04-45	△	△	20×20	20	125	24	5.0	4.0	ZR(T)HD05-□□		
	2525R/L04-45	△	△	25×25	25	150	29					
	3232R/L04-45	△	△	32×32	32	170	36					
QXKD	2020R/L04-45	△	△	20×20	20	125	24	6.0	4.0	ZR(T)KD06-□□		
	2525R/L04-45	△	△	25×25	25	150	29					
	3232R/L04-45	△	△	32×32	32	170	36					

▲Stock available △Make-to-order

External grooving tools for difficult-to-machine materials






R-type shown



Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}			
QEFS	2525R/L12-3N	△	△	25×25	25	150	25.3	3	12	ZIGQ3N-□□ ZIMF304N-□□	GB70-85-M6×20	WH50L
	3232R/L22-3N	△	△	32×32	32	170	32.3	3	22			
QEGS	2525R/L12-4N	△	△	25×25	25	150	25.3	4	12	ZIGQ4N-□□ ZIMF40□N-□□		
	3232R/L22-4N	△	△	32×32	32	170	32.3	4	22			
QEHS	2525R/L12-5N	△	△	25×25	25	150	25.4	5	12	ZIGQ5N-□□ ZIMF50□N-□□		
	3232R/L22-5N	△	△	32×32	32	170	32.4	5	22			
QEKs	2525R/L12-6N	△	△	25×25	25	150	25.4	6	12	ZIGQ6N-□□ ZIMF60□N-□□		
	3232R/L22-6N	△	△	32×32	32	170	32.4	6	22			

▲Stock available △Make-to-order

Blade for external parting





Type	Stock	Basic dimensions(mm)						Applicable inserts	Wrench
		LF	H	HF	B	W	CDX		
QES26N	▲	110	26	19	2	2.5	60	ZPES02502-MG	W50RL
QEFS26N	▲	110	26	19	2.4	3	60	ZPFS0302-MG	
QEGS26N	▲	110	26	19	3.2	4	70	ZPGS0402-MG	
QEHS26N	▲	110	26	19	4	5	70	ZPHS0503-MG	
QEKS26N	▲	110	26	19	5	6	70	ZPKS0604-MG	
QES32N	▲	150	32	24.6	2	2.5	100	ZPES02502-MG	
QEFS32N	▲	150	32	24.6	2.4	3	100	ZPFS0302-MG	
QEGS32N	▲	150	32	24.6	3.2	4	120	ZPGS0402-MG	
QEHS32N	▲	150	32	24.6	4	5	120	ZPHS0503-MG	
QEKS32N	▲	150	32	24.6	5	6	120	ZPKS0604-MG	

▲Stock available

△Make-to-order

Holder for blade of external parting



Type	Stock	Basic dimensions(mm)						Clamp	Screw	Wrench
		L	H	h1	h2	B	B1			
QZS2026	▲	86	20	10	46.6	19	38	QZC26	GB70-85-M6×20	WH50L
QZS2526	▲	86	25	5	46.6	23	42	QZC26		
QZS3226	▲	86	30	3	51.6	30	48	QZC26		
QZS2032	▲	110	20	13	50	19	38	QZC32		
QZS2532	▲	110	25	8	50	23	42	QZC32		
QZS3232	▲	110	32	5	54	30	48	QZC32		

▲Stock available

△Make-to-order

General turning

Parting and grooving

Little squirrel series parting and grooving tools





TURNING / Parting and grooving tools

Little squirrel series parting and grooving tools

End surface grooving and turning tools



L-type shown



Type		Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
QFFD	2020R/L7-48H	▲	▲	20×20	20	150	21	3	7	48-66	ZT(R)FD03□□-□□	GB70-85-M6×20	WH50L
	2020R/L10-48H	▲	▲	20×20	20	150	21	3	10	48-66			
	2020R/L7-60H	△	△	20×20	20	150	21	3	7	60-80			
	2020R/L10-60H	△	△	20×20	20	150	21	3	10	60-80			
	2020R/L7-74H	△	△	20×20	20	150	21	3	7	74-110			
	2020R/L10-74H	△	▲	20×20	20	150	21	3	10	74-110			
	2020R/L7-100H	△	△	20×20	20	150	21	3	7	100-150			
	2020R/L10-100H	△	△	20×20	20	150	21	3	10	100-150			
	2525R/L10-48H	▲	▲	25×25	25	150	26	3	10	48-66			
	2525R/L17-48H	▲	▲	25×25	25	150	26	3	17	48-66			
	2525R/L10-60H	▲	▲	25×25	25	150	26	3	10	60-80			
	2525R/L17-60H	▲	▲	25×25	25	150	26	3	17	60-80			
	2525R/L10-74H	▲	▲	25×25	25	150	26	3	10	74-110			
	2525R/L17-74H	▲	▲	25×25	25	150	26	3	17	74-110			
	2525R/L10-100H	▲	▲	25×25	25	150	26	3	10	100-150			
	2525R/L10-150H	△	△	25×25	25	150	26	3	10	150-260			
	2525R/L17-100H	▲	▲	25×25	25	150	26	3	17	100-150			
	2525R/L17-100H	△	△	25×25	25	150	26	3	17	150-260			
QFGD	2020R/L10-52H	△	△	20×20	20	150	21	4	10	52-72	ZT(R)GD04□□-□□	GB70-85-M6×20	WH50L
	2020R/L15-52H	△	△	20×20	20	150	21	4	15	52-72			
	2020R/L10-64H	△	▲	20×20	20	150	21	4	10	64-100			
	2020R/L15-64H	△	△	20×20	20	150	21	4	15	64-100			
	2020R/L10-90H	△	△	20×20	20	150	21	4	10	90-140			
	2020R/L15-90H	△	△	20×20	20	150	21	4	15	90-140			
	2020R/L10-130H	△	△	20×20	20	150	21	4	10	130-230			
	2020R/L15-130H	△	△	20×20	20	150	21	4	15	130-230			
	2525R/L13-52H	▲	▲	25×25	25	150	26	4	13	52-72			
	2525R/L22-52H	▲	▲	25×25	25	150	26	4	22	52-72			
	2525R/L13-64H	▲	▲	25×25	25	150	26	4	13	64-100			
	2525R/L22-64H	▲	▲	25×25	25	150	26	4	22	64-100			
	2525R/L13-90H	▲	▲	25×25	25	150	26	4	13	90-140			
	2525R/L22-90H	▲	▲	25×25	25	150	26	4	22	90-140			
	2525R/L13-130H	▲	▲	25×25	25	150	26	4	13	130-230			
	2525R/L22-130H	▲	▲	25×25	25	150	26	4	22	130-230			
	2525R/L13-220H	△	△	25×25	25	150	26	4	13	220-600			
	2525R/L22-220H	△	△	25×25	25	150	26	4	22	220-600			

▲Stock available



△Make-to-order



End surface grooving and turning tools



L-type shown



Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench	
		R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
QFHD	2525R/L13-58H	▲	▲	25×25	25	150	26	5	13	58-96	ZT(R)HD05□□-□□	GB70-85-M6×20	WH50L
	2525R/L22-58H	▲	▲	25×25	25	150	26	5	22	58-96			
	2525R/L13-86H	△	▲	25×25	25	150	26	5	13	86-140			
	2525R/L22-86H	▲	▲	25×25	25	150	26	5	22	86-140			
	2525R/L13-130H	▲	▲	25×25	25	150	26	5	13	130-200			
	2525R/L22-130H	▲	▲	25×25	25	150	26	5	22	130-200			
	2525R/L13-185H	▲	▲	25×25	25	150	26	5	13	185-400			
	2525R/L13-260H	△	△	25×25	25	150	26	5	13	260-1000			
	2525R/L22-185H	▲	▲	25×25	25	150	26	5	22	185-400			
	2525R/L22-260H	△	△	25×25	25	150	26	5	22	260-1000			
QFHS	2525R/L30-185H	△	△	25×25	25	150	26	5	30	185-400	ZTHS0504-MG		
QFKD	2525R/L13-60H	▲	▲	25×25	25	150	26	6	13	60-100	ZT(R)KD06□□-□□	GB70-85-M6×20	WH50L
	2525R/L22-60H	▲	▲	25×25	25	150	26	6	22	60-100			
	2525R/L13-88H	△	▲	25×25	25	150	26	6	13	88-180			
	2525R/L22-88H	▲	▲	25×25	25	150	26	6	22	88-180			
	2525R/L13-160H	▲	▲	25×25	25	150	26	6	13	160-400			
	2525R/L13-280H	△	△	25×25	25	150	26	6	13	280-1200			
	2525R/L22-160H	▲	▲	25×25	25	150	26	6	22	160-400			
	2525R/L22-280H	△	△	25×25	25	150	26	6	22	280-1200			
QFKS	2525R/L30-160H	△	△	25×25	25	150	26	6	30	160-400	ZTKS0608-MG		
QFLD	2525R/L25-75H	▲	▲	25×25	25	150	27	8	25	75-150	ZTLD0808-MM	GB70-85-M6×20	WH50L
	2525R/L25-140H	▲	▲	25×25	25	150	27	8	25	140-400	ZTLD0808-MM	GB70-85-M6×20	WH50L
	3232R/L28-140H	▲	▲	32×32	32	170	30	8	28	140-400	ZTLD0808-MM	GB70-85-M8×30	WH60L

▲Stock available △Make-to-order


General turning

Parting and grooving



Little squirrel series parting and grooving tools



End surface grooving and turning tools




RR-type shown





Type		Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench
			H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
QFFD	2020RR7-48H	△	20×20	20	150	21	3	7	48-66	ZT(R)FD03□□-□□	GB70-85-M6×20	WH50L
	2020RR10-48H	△	20×20	20	150	21	3	10	48-66			
	2020RR7-60H	△	20×20	20	150	21	3	7	60-80			
	2020RR10-60H	△	20×20	20	150	21	3	10	60-80			
	2020RR7-74H	△	20×20	20	150	21	3	7	74-110			
	2020RR10-74H	△	20×20	20	150	21	3	10	74-110			
	2020RR7-100H	△	20×20	20	150	21	3	7	100-150			
	2020RR10-100H	△	20×20	20	150	21	3	10	100-150			
	2525RR10-48H	△	25×25	25	150	26	3	10	48-66			
	2525RR17-48H	△	25×25	25	150	26	3	17	48-66			
	2525RR10-60H	△	25×25	25	150	26	3	10	60-80			
	2525RR17-60H	△	25×25	25	150	26	3	17	60-80			
	2525RR10-74H	△	25×25	25	150	26	3	10	74-110			
	2525RR17-74H	△	25×25	25	150	26	3	17	74-110			
	2525RR10-100H	△	25×25	25	150	26	3	10	100-150			
	2525RR17-100H	△	25×25	25	150	26	3	17	100-150			
QFGD	2020RR10-52H	△	20×20	20	150	21	4	10	52-72	ZT(R)GD04□□-□□		
	2020RR15-52H	△	20×20	20	150	26	4	15	52-72			
	2020RR10-64H	△	20×20	20	150	21	4	10	64-100			
	2020RR15-64H	△	20×20	20	150	26	4	15	64-100			
	2020RR10-90H	△	20×20	20	150	21	4	10	90-140			
	2020RR15-90H	△	20×20	20	150	26	4	15	90-140			
	2020RR10-130H	△	20×20	20	150	21	4	10	130-230			
	2020RR15-130H	△	20×20	20	150	26	4	15	130-230			
	2525RR13-52H	△	25×25	25	150	21	4	13	52-72			
	2525RR22-52H	△	25×25	25	150	26	4	22	52-72			
	2525RR13-64H	△	25×25	25	150	21	4	13	64-100			
	2525RR22-64H	△	25×25	25	150	26	4	22	64-100			
	2525RR13-90H	△	25×25	25	150	21	4	13	90-140			
	2525RR22-90H	△	25×25	25	150	26	4	22	90-140			
	2525RR13-130H	△	25×25	25	150	21	4	13	130-230			
	2525RR22-130H	△	25×25	25	150	26	4	22	130-230			

▲Stock available △Make-to-order

End surface grooving and turning tools



RR-type shown



Diameter range of entering



Type	Stock	Basic dimensions(mm)								Applicable inserts	Screw	Wrench
		H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)				
QFHD	2525RR13-58H	△	25×25	25	150	26	5	13	58-96	ZT(R)HD05□□-□□	GB70-85-M6×20	WH50L
	2525RR22-58H	△	25×25	25	150	26	5	22	58-96			
	2525RR13-86H	△	25×25	25	150	26	5	13	86-140			
	2525RR22-86H	△	25×25	25	150	26	5	22	86-140			
	2525RR13-130H	△	25×25	25	150	26	5	13	130-200			
	2525RR22-130H	△	25×25	25	150	26	5	22	130-200			
	2525RR13-185H	△	25×25	25	150	26	5	13	185-400			
	2525RR22-185H	△	25×25	25	150	26	5	22	185-400			
QFHS	2525RR30-185H	△	25×25	25	150	26	5	30	185-400	ZTHS0504-MG		
QFKD	2525RR13-60H	△	25×25	25	150	26	6	13	60-100	ZT(R)KD06□□-□□	GB70-85-M6×20	WH50L
	2525RR22-60H	△	25×25	25	150	26	6	22	60-100			
	2525RR13-88H	△	25×25	25	150	26	6	13	88-180			
	2525RR22-88H	△	25×25	25	150	26	6	22	88-180			
	2525RR13-160H	△	25×25	25	150	26	6	13	160-400			
	2525RR22-160H	△	25×25	25	150	26	6	22	160-400			
QFKS	2525RR30-160H	△	25×25	25	150	26	6	30	160-400	ZTKS0608-MG		

▲ Stock available

△ Make-to-order

General turning

Parting and grooving


Little squirrel series parting and grooving tools



End surface grooving and turning tools



LL-type shown



Diameter range of entering




Type		Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench		
			H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)					
QFFD	2020LL7-48H	△	20×20	20	150	21	3	7	48-66	ZT(R)FD03□□-□□	GB70-85-M6×20	WH50L		
	2020LL10-48H	△	20×20	20	150	21	3	10	48-66					
	2020LL7-60H	△	20×20	20	150	21	3	7	60-80					
	2020LL10-60H	△	20×20	20	150	21	3	10	60-80					
	2020LL7-74H	△	20×20	20	150	21	3	7	74-110					
	2020LL10-74H	△	20×20	20	150	21	3	10	74-110					
	2020LL7-100H	△	20×20	20	150	21	3	7	100-150					
	2020LL10-100H	△	20×20	20	150	21	3	10	100-150					
	2525LL10-48H	△	25×25	25	150	26	3	10	48-66					
	2525LL17-48H	△	25×25	25	150	26	3	17	48-66					
	2525LL10-60H	△	25×25	25	150	26	3	10	60-80					
	2525LL17-60H	△	25×25	25	150	26	3	17	60-80					
	2525LL10-74H	△	25×25	25	150	26	3	10	74-110					
	2525LL17-74H	△	25×25	25	150	26	3	17	74-110					
	2525LL10-100H	△	25×25	25	150	26	3	10	100-150					
	2525LL17-100H	△	25×25	25	150	26	3	17	100-150					
QFGD	2020LL10-52H	△	20×20	20	150	21	4	10	52-72	ZT(R)GD04□□-□□				
	2020LL15-52H	△	20×20	20	150	26	4	15	52-72					
	2020LL10-64H	△	20×20	20	150	21	4	10	64-100					
	2020LL15-64H	△	20×20	20	150	26	4	15	64-100					
	2020LL10-90H	△	20×20	20	150	21	4	10	90-140					
	2020LL15-90H	△	20×20	20	150	26	4	15	90-140					
	2020LL10-130H	△	20×20	20	150	21	4	10	130-230					
	2020LL15-130H	△	20×20	20	150	26	4	15	130-230					
	2525LL13-52H	△	25×25	25	150	21	4	13	52-72					
	2525LL22-52H	△	25×25	25	150	26	4	22	52-72					
	2525LL13-64H	△	25×25	25	150	21	4	13	64-100					
	2525LL22-64H	△	25×25	25	150	26	4	22	64-100					
	2525LL13-90H	△	25×25	25	150	21	4	13	90-140					
	2525LL22-90H	△	25×25	25	150	26	4	22	90-140					
	2525LL13-130H	△	25×25	25	150	21	4	13	130-230					
	2525LL22-130H	△	25×25	25	150	26	4	22	130-230					


▲Stock available

△Make-to-order

End surface grooving and turning tools



LL-type shown



Diameter range of entering



Type	Stock	Basic dimensions(mm)								Applicable inserts	Screw	Wrench
		H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)				
QFHD	2525LL13-58H	△	25×25	25	150	26	5	13	58-96	ZT(R)HD05□□-□□	GB70-85-M6×20	WH50L
	2525LL22-58H	△	25×25	25	150	26	5	22	58-96			
	2525LL13-86H	△	25×25	25	150	26	5	13	86-140			
	2525LL22-86H	△	25×25	25	150	26	5	22	86-140			
	2525LL13-130H	△	25×25	25	150	26	5	13	130-200			
	2525LL22-130H	△	25×25	25	150	26	5	22	130-200			
	2525LL13-185H	△	25×25	25	150	26	5	13	185-400			
	2525LL22-185H	△	25×25	25	150	26	5	22	185-400			
QFHS	2525LL30-185H	△	25×25	25	150	26	5	30	185-400	ZTHS0504-MG		
QFKD	2525LL13-60H	△	25×25	25	150	26	6	13	60-100	ZT(R)KD06□□-□□	GB70-85-M6×20	WH50L
	2525LL22-60H	△	25×25	25	150	26	6	22	60-100			
	2525LL13-88H	△	25×25	25	150	26	6	13	88-180			
	2525LL22-88H	△	25×25	25	150	26	6	22	88-180			
	2525LL13-160H	△	25×25	25	150	26	6	13	160-400			
	2525LL22-160H	△	25×25	25	150	26	6	22	160-400			
QFKS	2525LL30-160H	△	25×25	25	150	26	6	30	160-400	ZTKS0608-MG		

▲ Stock available

△ Make-to-order

General turning

Parting and grooving



Little squirrel series parting and grooving tools



L type tools for surface grooving and turning



R-type shown



Diameter range of entering




Type		Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
QFFD	2020R/L7-48L	△	△	20×20	20	150	28.5	3	7	48-66	ZT(R)FD03□□-□□	GB70-85-M6×20	WH50L
	2020R/L10-48L	△	△	20×20	20	150	31.5	3	10	48-66			
	2020R/L7-60L	△	△	20×20	20	150	28.5	3	7	60-80			
	2020R/L10-60L	△	△	20×20	20	150	31.5	3	10	60-80			
	2020R/L7-74L	△	△	20×20	20	150	28.5	3	7	74-110			
	2020R/L10-74L	△	△	20×20	20	150	31.5	3	10	74-110			
	2020R/L7-100L	△	△	20×20	20	150	28.5	3	7	100-150			
	2020R/L10-100L	△	△	20×20	20	150	31.5	3	10	100-150			
	2525R/L10-48L	▲	▲	25×25	25	150	36.5	3	10	48-66			
	2525R/L17-48L	△	△	25×25	25	150	43.5	3	17	48-66			
	2525R/L10-60L	▲	▲	25×25	25	150	36.5	3	10	60-80			
	2525R/L17-60L	△	△	25×25	25	150	43.5	3	17	60-80			
	2525R/L10-74L	▲	▲	25×25	25	150	36.5	3	10	74-110			
	2525R/L17-74L	△	△	25×25	25	150	43.5	3	17	74-110			
	2525R/L10-100L	▲	▲	25×25	25	150	36.5	3	10	100-150			
	2525R/L17-100L	△	△	25×25	25	150	43.5	3	17	100-150			
QFGD	2020R/L10-52L	△	△	20×20	20	150	31.5	4	10	52-72	ZT(R)GD04□□-□□	GB70-85-M6×20	WH50L
	2020R/L15-52L	△	△	20×20	20	150	36.5	4	15	52-72			
	2020R/L10-64L	△	△	20×20	20	150	31.5	4	10	64-100			
	2020R/L15-64L	△	△	20×20	20	150	36.5	4	15	64-100			
	2020R/L10-90L	△	△	20×20	20	150	31.5	4	10	90-140			
	2020R/L15-90L	△	△	20×20	20	150	36.5	4	15	90-140			
	2020R/L10-130L	△	△	20×20	20	150	31.5	4	10	130-230			
	2020R/L15-130L	△	△	20×20	20	150	36.5	4	15	130-230			
	2525R/L13-52L	▲	△	25×25	25	150	39.5	4	13	52-72			
	2525R/L22-52L	△	△	25×25	25	150	48.5	4	22	52-72			
	2525R/L13-64L	△	△	25×25	25	150	39.5	4	13	64-100			
	2525R/L22-64L	△	△	25×25	25	150	48.5	4	22	64-100			
	2525R/L13-90L	△	△	25×25	25	150	39.5	4	13	90-140			
	2525R/L22-90L	▲	△	25×25	25	150	48.5	4	22	90-140			
	2525R/L13-130L	△	△	25×25	25	150	39.5	4	13	130-230			
	2525R/L22-130L	▲	▲	25×25	25	150	48.5	4	22	130-230			


▲Stock available

△Make-to-order

L type tools for surface grooving and turning



R-type shown



Diameter range of entering



Type		Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
		R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
QFHD	2525R/L13-58L	△	△	25×25	25	150	39.5	5	13	58-96	ZT(R)HD05□□-□□	GB70-85-M6×20	WH50L
	2525R/L22-58L	△	△	25×25	25	150	48.5	5	22	58-96			
	2525R/L13-86L	△	△	25×25	25	150	39.5	5	13	86-140			
	2525R/L22-86L	△	△	25×25	25	150	48.5	5	22	86-140			
	2525R/L13-130L	△	△	25×25	25	150	39.5	5	13	130-200			
	2525R/L22-130L	△	△	25×25	25	150	48.5	5	22	130-200			
	2525R/L13-185L	△	△	25×25	25	150	39.5	5	13	185-400			
	2525R/L22-185L	▲	△	25×25	25	150	48.5	5	22	185-400			
QFHS	2525R/L30-185L	△	△	25×25	25	150	56.5	5	30	185-400	ZTHS0504-MG		
QFKD	2525R/L13-60L	▲	▲	25×25	25	150	39.5	6	13	60-100	ZT(R)KD06□□-□□	GB70-85-M6×20	WH50L
	2525R/L22-60L	▲	▲	25×25	25	150	48.5	6	22	60-100			
	2525R/L13-88L	△	▲	25×25	25	150	39.5	6	13	88-180			
	2525R/L22-88L	▲	▲	25×25	25	150	48.5	6	22	88-180			

▲Stock available △Make-to-order

General turning

Parting and grooving


Little squirrel series parting and grooving tools



Internal grooving and turning tools



R-type shown



Type	Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench
	R	L	DCON	LF	WF	CW	CDX _{max}	DMIN			
C20Q-QEDR/L05-27	▲	▲	20	180	15.2	2.5	5	27	ZTED025□□ ZRED025□□	GB70-85-M4×12	WH30L
C25R-QEDR/L07-33	▲	▲	25	200	20.3	2.5	7	33		GB70-85-M5×16	WH40L
C32S-QEDR/L09-42	▲	▲	32	250	25.3	2.5	9	42		GB70-85-M5×20	WH40L
C20Q-QFDR/L05-27	▲	▲	20	180	15.2	3	5	27	ZTFD03□□ ZRFD03□□	GB70-85-M4×12	WH30L
C25R-QFDR/L07-33	▲	▲	25	200	20.3	3	7	33		GB70-85-M5×16	WH40L
C32S-QFDR/L09-42	▲	▲	32	250	25.3	3	9	42		GB70-85-M5×20	WH40L
C25R-QGDR/L08-35	▲	▲	25	200	21.5	4	8	35	ZTGD04□□ ZRGD04□□	GB70-85-M5×16	WH40L
C32S-QGDR/L11-44	▲	▲	32	250	27.5	4	11	44		GB70-85-M6×20	WH50L
C40T-QGDR/L13-54	▲	▲	40	300	33.5	4	13	54		GB70-85-M6×20	WH50L
C25R-QHDR/L08-35	▲	▲	25	200	21.5	5	8	35	ZTHD05□□ ZRHD05□□	GB70-85-M5×16	WH40L
C32S-QHDR/L11-44	▲	▲	32	250	27.5	5	11	44		GB70-85-M6×20	WH50L
C40T-QHDR/L13-54	▲	▲	40	300	33.5	5	13	54		GB70-85-M6×20	WH50L
C25R-QKDR/L08-35	▲	▲	25	200	21.5	6	8	35	ZTKD06□□ ZRKD06□□	GB70-85-M5×16	WH40L
C32S-QKDR/L11-44	▲	▲	32	250	27.5	6	11	44		GB70-85-M6×20	WH50L
C40T-QKDR/L13-54	▲	▲	40	300	33.5	6	13	54		GB70-85-M6×20	WH50L


▲ Stock available

△ Make-to-order

Profile turning tools for Al



R-type shown



Type	Stock		Basic dimensions(mm)					Applicable inserts	Screw	Wrench
	R	L	DMIN (Minimum machining diameter)	DCON	WF	LF	CDX			
C40X-QLDR/L65-15A	▲	▲	160	40	21	320	65	ZRLD08-LH	GB70-85-M6×20	WH50L
C40X-QLDR/L80-15A	▲	△	160	40	21	320	80	ZRLD08-LH		
C40X-QKDR/L60-15A	△	△	160	40	20	320	60	ZRKD06-LH		
C40X-QKDR/L75-15A	△	△	160	40	20	320	75	ZRKD06-LH		



▲ Stock available

△ Make-to-order

External parting, grooving and turning tools



L-type shown



Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
	R	L	H×B	LF	WF	CW	CDX	ØD	CDX			
GED1616R/L08-2.5	▲	▲	16×16	125	16.3	2.5	8	∞	8	G□MD25□□-□□	GB70-85-M5×16	WH40L
GED1616R/L14-2.5	▲	▲	16×16	125	16.3	2.5	14	60	11			
GED2020R/L08-2.5	▲	▲	20×20	125	20.3	2.5	8	∞	8			
GED2020R/L14-2.5	▲	▲	20×20	125	20.3	2.5	14	100	11			
GED2525R/L08-2.5	▲	▲	25×25	150	25.3	2.5	8	∞	8			
GED2525R/L14-2.5	▲	▲	25×25	150	25.3	2.5	14	100	11			
GED1616R/L08-3	▲	▲	16×16	125	16.45	3	8	∞	8	G□MD3□□-□□	GB70-85-M5×16	WH40L
GED1616R/L14-3	▲	▲	16×16	125	16.45	3	14	60	11			
GED2020R/L08-3	▲	▲	20×20	125	20.45	3	8	∞	8			
GED2020R/L14-3	▲	▲	20×20	125	20.45	3	14	100	11			
GED2525R/L08-3	▲	▲	25×25	150	25.45	3	8	∞	8			
GED2525R/L14-3	▲	▲	25×25	150	25.45	3	14	100	11			
GED2020R/L10-4	▲	▲	20×20	125	20.5	4	10	∞	10	G□MD4□□-□□	GB70-85-M6×20	WH50L
GED2020R/L17-4	▲	▲	20×20	125	20.5	4	17	100	14			
GED2525R/L10-4	▲	▲	25×25	150	25.5	4	10	∞	10			
GED2525R/L17-4	▲	▲	25×25	150	25.5	4	17	100	14			
GED3232R/L10-4	▲	▲	32×32	170	32.5	4	10	∞	10			
GED3232R/L17-4	▲	▲	32×32	170	32.5	4	17	∞	17			
GED2525R/L10-5	▲	▲	25×25	150	25.5	5	10	∞	10	G□MD5□□-□□	GB70-85-M6×20	WH50L
GED2525R/L17-5	▲	▲	25×25	150	25.5	5	17	100	14			
GED3232R/L10-5	▲	▲	32×32	170	32.5	5	10	∞	10			
GED3232R/L17-5	▲	▲	32×32	170	32.5	5	17	∞	17			
GED2525R/L10-6	▲	▲	25×25	150	25.5	6	10	∞	10	G□MD6□□-□□	GB70-85-M6×20	WH50L
GED2525R/L17-6	▲	▲	25×25	150	25.5	6	17	100	14			
GED3232R/L10-6	▲	▲	32×32	170	32.5	6	10	∞	10			
GED3232R/L17-6	▲	▲	32×32	170	32.5	6	17	∞	17			

▲Stock available

△Make-to-order

General turning

Parting and grooving



G-series parting and grooving tools



End surface grooving and turning tools



L-type shown



Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench		
	R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)					
GFD2020R/L08-28H-3	△	△	20×20	20	150	21	3	8	28-35	G□MD3□□-□□	GB70-85-M6×20	WH50L		
GFD2020R/L08-34H-3	△	△	20×20	20	150	21	3	8	34-45					
GFD2020R/L08-44H-3	△	△	20×20	20	150	21	3	8	44-60					
GFD2020R/L14-58H-3	△	△	20×20	20	150	21	3	14	58-80					
GFD2020R/L14-78H-3	△	△	20×20	20	150	21	3	14	78-130					
GFD2020R/L14-126H-3	△	△	20×20	20	150	21	3	14	126-230					
GFD2525R/L08-28H-3	▲	▲	25×25	25	150	26	3	8	28-35					
GFD2525R/L08-34H-3	▲	▲	25×25	25	150	26	3	8	34-45					
GFD2525R/L08-44H-3	▲	▲	25×25	25	150	26	3	8	44-60					
GFD2525R/L14-58H-3	▲	▲	25×25	25	150	26	3	14	58-80					
GFD2525R/L14-78H-3	▲	▲	25×25	25	150	26	3	14	78-130					
GFD2525R/L14-126H-3	▲	▲	25×25	25	150	26	3	14	126-230					
GFD2020R/L10-28H-4	△	△	20×20	20	150	21	4	10	28-35	G□MD4□□-□□				
GFD2020R/L10-34H-4	△	△	20×20	20	150	21	4	10	34-45					
GFD2020R/L10-44H-4	△	△	20×20	20	150	21	4	10	44-60					
GFD2020R/L17-58H-4	△	△	20×20	20	150	21	4	17	58-80					
GFD2020R/L17-78H-4	△	△	20×20	20	150	21	4	17	78-130					
GFD2020R/L17-126H-4	△	△	20×20	20	150	21	4	17	126-230					
GFD2525R/L10-28H-4	▲	▲	25×25	25	150	26	4	10	28-35					
GFD2525R/L10-34H-4	▲	▲	25×25	25	150	26	4	10	34-45					
GFD2525R/L10-44H-4	▲	▲	25×25	25	150	26	4	10	44-60					
GFD2525R/L17-58H-4	▲	▲	25×25	25	150	26	4	17	58-80					
GFD2525R/L17-78H-4	▲	▲	25×25	25	150	26	4	17	78-130					
GFD2525R/L17-126H-4	▲	▲	25×25	25	150	26	4	17	126-230					
GFD2525R/L17-200H-4	▲	▲	25×25	25	150	26	4	17	200-480					


▲ Stock available

△ Make-to-order

End surface grooving and turning tools



L-type shown



Diameter range of entering



General turning

Parting and grooving

G-series parting and grooving tools

Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
	R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
GFD2020R/L10-35H-5	△	△	20×20	20	150	21	5	10	35-45	G□MD5□□-□□	GB70-85-M6×20	WH50L
GFD2020R/L10-44H-5	△	△	20×20	20	150	21	5	10	44-58			
GFD2020R/L17-56H-5	△	△	20×20	20	150	21	5	17	56-86			
GFD2020R/L17-84H-5	△	△	20×20	20	150	21	5	17	84-158			
GFD2020R/L17-156H-5	△	△	20×20	20	150	21	5	17	156-500			
GFD2525R/L10-35H-5	▲	▲	25×25	25	150	26	5	10	35-45			
GFD2525R/L10-44H-5	▲	▲	25×25	25	150	26	5	10	44-58			
GFD2525R/L17-56H-5	▲	▲	25×25	25	150	26	5	17	56-86			
GFD2525R/L17-84H-5	▲	▲	25×25	25	150	26	5	17	84-158			
GFD2525R/L17-156H-5	▲	▲	25×25	25	150	26	5	17	156-500			
GFD2020R/L10-35H-6	△	△	20×20	20	150	21	6	10	35-50	G□MD6□□-□□	GB70-85-M6×20	WH50L
GFD2020R/L17-48H-6	△	△	20×20	20	150	21	6	17	48-80			
GFD2020R/L17-78H-6	△	△	20×20	20	150	21	6	17	78-168			
GFD2020R/L17-160H-6	△	△	20×20	20	150	21	6	17	160-660			
GFD2525R/L10-35H-6	▲	▲	25×25	25	150	26	6	10	35-50			
GFD2525R/L17-48H-6	▲	▲	25×25	25	150	26	6	17	48-80			
GFD2525R/L17-78H-6	▲	▲	25×25	25	150	26	6	17	78-168			
GFD2525R/L17-160H-6	▲	▲	25×25	25	150	26	6	17	160-660			

▲Stock available



△Make-to-order



End surface grooving and turning tools



RR-type shown



Diameter range of entering



Type	Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench		
		H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)					
GFD2020RR08-28H-3	△	20×20	20	150	21	3	8	28-35	G□MD3□□-□□	GB70-85-M6x20	WH50L		
GFD2020RR08-34H-3	△	20×20	20	150	21	3	8	34-45					
GFD2020RR08-44H-3	△	20×20	20	150	21	3	8	44-60					
GFD2020RR14-58H-3	△	20×20	20	150	21	3	14	58-80					
GFD2020RR14-78H-3	△	20×20	20	150	21	3	14	78-130					
GFD2020RR14-126H-3	△	20×20	20	150	21	3	14	126-230					
GFD2525RR08-28H-3	△	25×25	25	150	26	3	8	28-35					
GFD2525RR08-34H-3	△	25×25	25	150	26	3	8	34-45					
GFD2525RR08-44H-3	△	25×25	25	150	26	3	8	44-60					
GFD2525RR14-58H-3	△	25×25	25	150	26	3	14	58-80					
GFD2525RR14-78H-3	△	25×25	25	150	26	3	14	78-130					
GFD2525RR14-126H-3	△	25×25	25	150	26	3	14	126-230					
GFD2020RR10-28H-4	△	20×20	20	150	21	4	10	28-35	G□MD4□□-□□				
GFD2020RR10-34H-4	△	20×20	20	150	21	4	10	34-45					
GFD2020RR10-44H-4	△	20×20	20	150	21	4	10	44-60					
GFD2020RR17-58H-4	△	20×20	20	150	21	4	17	58-80					
GFD2020RR17-78H-4	△	20×20	20	150	21	4	17	78-130					
GFD2020RR17-126H-4	△	20×20	20	150	21	4	17	126-230					
GFD2525RR10-28H-4	△	25×25	25	150	26	4	10	28-35					
GFD2525RR10-34H-4	△	25×25	25	150	26	4	10	34-45					
GFD2525RR10-44H-4	△	25×25	25	150	26	4	10	44-60					
GFD2525RR17-58H-4	△	25×25	25	150	26	4	17	58-80					
GFD2525RR17-78H-4	△	25×25	25	150	26	4	17	78-130					
GFD2525RR17-126H-4	△	25×25	25	150	26	4	17	126-230					
GFD2525RR17-200H-4	△	25×25	25	150	26	4	17	200-480					


▲ Stock available △ Make-to-order



End surface grooving and turning tools



RR-type shown



Diameter range of entering



Type	Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench
		H×B	HF	LF	WF	CW	CDX _{max}	∅D (min-max)			
GFD2020RR10-35H-5	△	20×20	20	150	21	5	10	35-45	G□MD5□□-□□	GB70-85-M6x20	WH50L
GFD2020RR10-44H-5	△	20×20	20	150	21	5	10	44-58			
GFD2020RR17-56H-5	△	20×20	20	150	21	5	17	56-86			
GFD2020RR17-84H-5	△	20×20	20	150	21	5	17	84-158			
GFD2020RR17-156H-5	△	20×20	20	150	21	5	17	156-500			
GFD2525RR10-35H-5	△	25×25	25	150	26	5	10	35-45			
GFD2525RR10-44H-5	△	25×25	25	150	26	5	10	44-58			
GFD2525RR17-56H-5	△	25×25	25	150	26	5	17	56-86			
GFD2525RR17-84H-5	△	25×25	25	150	26	5	17	84-158			
GFD2525RR17-156H-5	△	25×25	25	150	26	5	17	156-500			
GFD2020RR10-35H-6	△	20×20	20	150	21	6	10	35-50	G□MD6□□-□□		
GFD2020RR17-48H-6	△	20×20	20	150	21	6	17	48-80			
GFD2020RR17-78H-6	△	20×20	20	150	21	6	17	78-168			
GFD2020RR17-160H-6	△	20×20	20	150	21	6	17	160-660			
GFD2525RR10-35H-6	△	25×25	25	150	26	6	10	35-50			
GFD2525RR17-48H-6	△	25×25	25	150	26	6	17	48-80			
GFD2525RR17-78H-6	△	25×25	25	150	26	6	17	78-168			
GFD2525RR17-160H-6	△	25×25	25	150	26	6	17	160-660			

▲Stock available △Make-to-order

General turning

Parting and grooving


G-series parting and grooving tools



End surface grooving and turning tools



LL-type shown



Type	Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench		
		H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)					
GFD2020LL08-28H-3	△	20×20	20	150	21	3	8	28-35	G□MD3□□-□□	GB70-85-M6x20	WH50L		
GFD2020LL08-34H-3	△	20×20	20	150	21	3	8	34-45					
GFD2020LL08-44H-3	△	20×20	20	150	21	3	8	44-60					
GFD2020LL14-58H-3	△	20×20	20	150	21	3	14	58-80					
GFD2020LL14-78H-3	△	20×20	20	150	21	3	14	78-130					
GFD2020LL14-126H-3	△	20×20	20	150	21	3	14	126-230					
GFD2525LL08-28H-3	△	25×25	25	150	26	3	8	28-35					
GFD2525LL08-34H-3	△	25×25	25	150	26	3	8	34-45					
GFD2525LL08-44H-3	△	25×25	25	150	26	3	8	44-60					
GFD2525LL14-58H-3	△	25×25	25	150	26	3	14	58-80					
GFD2525LL14-78H-3	△	25×25	25	150	26	3	14	78-130					
GFD2525LL14-126H-3	△	25×25	25	150	26	3	14	126-230					
GFD2020LL10-28H-4	△	20×20	20	150	21	4	10	28-35	G□MD4□□-□□				
GFD2020LL10-34H-4	△	20×20	20	150	21	4	10	34-45					
GFD2020LL10-44H-4	△	20×20	20	150	21	4	10	44-60					
GFD2020LL17-58H-4	△	20×20	20	150	21	4	17	58-80					
GFD2020LL17-78H-4	△	20×20	20	150	21	4	17	78-130					
GFD2020LL17-126H-4	△	20×20	20	150	21	4	17	126-230					
GFD2525LL10-28H-4	△	25×25	25	150	26	4	10	28-35					
GFD2525LL10-34H-4	△	25×25	25	150	26	4	10	34-45					
GFD2525LL10-44H-4	△	25×25	25	150	26	4	10	44-60					
GFD2525LL17-58H-4	△	25×25	25	150	26	4	17	58-80					
GFD2525LL17-78H-4	△	25×25	25	150	26	4	17	78-130					
GFD2525LL17-126H-4	△	25×25	25	150	26	4	17	126-230					
GFD2525LL17-200H-4	△	25×25	25	150	26	4	17	200-480					

▲Stock available


△Make-to-order



End surface grooving and turning tools



LL-type shown



Diameter range of entering



Type	Stock	Basic dimensions(mm)							Applicable inserts	Screw	Wrench
		H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
GFD2020LL10-35H-5	△	20×20	20	150	21	5	10	35-45	G□MD5□□-□□	GB70-85-M6x20	WH50L
GFD2020LL10-44H-5	△	20×20	20	150	21	5	10	44-58			
GFD2020LL17-56H-5	△	20×20	20	150	21	5	17	56-86			
GFD2020LL17-84H-5	△	20×20	20	150	21	5	17	84-158			
GFD2020LL17-156H-5	△	20×20	20	150	21	5	17	156-500			
GFD2525LL10-35H-5	△	25×25	25	150	26	5	10	35-45			
GFD2525LL10-44H-5	△	25×25	25	150	26	5	10	44-58			
GFD2525LL17-56H-5	△	25×25	25	150	26	5	17	56-86			
GFD2525LL17-84H-5	△	25×25	25	150	26	5	17	84-158			
GFD2525LL17-156H-5	△	25×25	25	150	26	5	17	156-500			
GFD2020LL10-35H-6	△	20×20	20	150	21	6	10	35-50	G□MD6□□-□□		
GFD2020LL17-48H-6	△	20×20	20	150	21	6	17	48-80			
GFD2020LL17-78H-6	△	20×20	20	150	21	6	17	78-168			
GFD2020LL17-160H-6	△	20×20	20	150	21	6	17	160-660			
GFD2525LL10-35H-6	△	25×25	25	150	26	6	10	35-50			
GFD2525LL17-48H-6	△	25×25	25	150	26	6	17	48-80			
GFD2525LL17-78H-6	△	25×25	25	150	26	6	17	78-168			
GFD2525LL17-160H-6	△	25×25	25	150	26	6	17	160-660			

▲Stock available

△Make-to-order

General turning

Parting and grooving


G-series parting and grooving tools



L type tools for surface grooving and turning



R-type shown



Diameter range of entering



Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench		
	R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)					
GFD2020R/L08-28L-3	△	△	20×20	20	150	29	3	8	28-35	G□MD3□□-□□	GB70-85-M6×20	WH50L		
GFD2020R/L08-34L-3	△	△	20×20	20	150	29	3	8	34-45					
GFD2020R/L08-44L-3	△	△	20×20	20	150	29	3	8	44-60					
GFD2020R/L14-58L-3	△	△	20×20	20	150	35	3	14	58-80					
GFD2020R/L14-78L-3	△	△	20×20	20	150	35	3	14	78-130					
GFD2020R/L14-126L-3	△	△	20×20	20	150	35	3	14	126-230					
GFD2525R/L08-28L-3	△	△	25×25	25	150	34	3	8	28-35					
GFD2525R/L08-34L-3	△	△	25×25	25	150	34	3	8	34-45					
GFD2525R/L08-44L-3	△	△	25×25	25	150	34	3	8	44-60					
GFD2525R/L14-58L-3	△	△	25×25	25	150	40	3	14	58-80					
GFD2525R/L14-78L-3	△	△	25×25	25	150	40	3	14	78-130					
GFD2525R/L14-126L-3	△	△	25×25	25	150	40	3	14	126-230					
GFD2020R/L10-28L-4	△	△	20×20	20	150	31	4	10	28-35	G□MD4□□-□□				
GFD2020R/L10-34L-4	△	△	20×20	20	150	31	4	10	34-45					
GFD2020R/L10-44L-4	△	△	20×20	20	150	31	4	10	44-60					
GFD2020R/L17-58L-4	△	△	20×20	20	150	38	4	17	58-80					
GFD2020R/L17-78L-4	△	△	20×20	20	150	38	4	17	78-130					
GFD2020R/L17-126L-4	△	△	20×20	20	150	38	4	17	126-230					
GFD2525R/L10-28L-4	△	△	25×25	25	150	36	4	10	28-35					
GFD2525R/L10-34L-4	△	△	25×25	25	150	36	4	10	34-45					
GFD2525R/L10-44L-4	△	△	25×25	25	150	36	4	10	44-60					
GFD2525R/L17-58L-4	△	△	25×25	25	150	43	4	17	58-80					
GFD2525R/L17-78L-4	△	△	25×25	25	150	43	4	17	78-130					
GFD2525R/L17-126L-4	△	△	25×25	25	150	43	4	17	126-230					
GFD2525R/L17-200L-4	△	△	25×25	25	150	43	4	17	200-480					


▲ Stock available

△ Make-to-order

L type tools for surface grooving and turning



R-type shown



Diameter range of entering



Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
	R	L	H×B	HF	LF	WF	CW	CDX _{max}	ØD (min-max)			
GFD2020R/L10-35L-5	△	△	20×20	20	150	31	5	10	35-45	G□MD5□□-□□	GB70-85-M6×20	WH50L
GFD2020R/L10-44L-5	△	△	20×20	20	150	31	5	10	44-58			
GFD2020R/L17-56L-5	△	△	20×20	20	150	38	5	17	56-86			
GFD2020R/L17-84L-5	△	△	20×20	20	150	38	5	17	84-158			
GFD2020R/L17-156L-5	△	△	20×20	20	150	38	5	17	156-500			
GFD2525R/L10-35L-5	△	△	25×25	25	150	36	5	10	35-45			
GFD2525R/L10-44L-5	△	△	25×25	25	150	43	5	10	44-58			
GFD2525R/L17-56L-5	△	△	25×25	25	150	43	5	17	56-86			
GFD2525R/L17-84L-5	△	△	25×25	25	150	43	5	17	84-158			
GFD2525R/L17-156L-5	△	△	25×25	25	150	43	5	17	156-500			
GFD2020R/L10-35L-6	△	△	20×20	20	150	31	6	10	35-50	G□MD6□□-□□	GB70-85-M6×20	WH50L
GFD2020R/L17-48L-6	△	△	20×20	20	150	38	6	17	48-80			
GFD2020R/L17-78L-6	△	△	20×20	20	150	38	6	17	78-168			
GFD2020R/L17-160L-6	△	△	20×20	20	150	38	6	17	160-660			
GFD2525R/L10-35L-6	△	△	25×25	25	150	36	6	10	35-50			
GFD2525R/L17-48L-6	△	△	25×25	25	150	43	6	17	48-80			
GFD2525R/L17-78L-6	△	△	25×25	25	150	43	6	17	78-168			
GFD2525R/L17-160L-6	△	△	25×25	25	150	43	6	17	160-660			

▲Stock available △Make-to-order

General turning

Parting and grooving


G-series parting and grooving tools



Internal grooving and turning tools



R-type shown




Type	Stock		Basic dimensions(mm)							Applicable inserts	Screw	Wrench
	R	L	CW	DMIN	DCON	LF	LH	WF	CDX			
GID2016R/L04-2.5	▲	▲	2.5	20	16	150	25	12	4	G□MD25□□-□□	I60M5×13	WT20IP
GID2520R/L05-2.5	▲	▲	2.5	25	20	180	30	15	5		GB70-85-M4×12	WH30L
GID3225R/L07-2.5	▲	▲	2.5	32	25	200	40	19.5	7		GB70-85-M5×12	WH40L
GID2016R/L05-3	▲	▲	3.0	20	16	150	25	12	5	G□MD3□□-□□	I60M5×13	WT20IP
GID2520R/L06-3	▲	▲	3.0	25	20	180	30	16	6		GB70-85-M4×12	WH30L
GID3225R/L08-3	▲	▲	3.0	32	25	200	40	20.5	8		GB70-85-M5×12	WH40L
GID2520R/L06-4	▲	▲	4.0	25	20	180	30	16	6	G□MD4□□-□□	GB70-85-M4×12	WH30L
GID3225R/L08-4	▲	▲	4.0	32	25	200	40	20.5	8		GB70-85-M5×12	WH40L
GID4032R/L11-4	▲	▲	4.0	40	32	250	50	27	11		GB70-85-M6×14	WH50L
GID3225R/L08-5	▲	▲	5.0	32	25	200	40	20.5	8	G□MD5□□-□□	GB70-85-M5×12	WH40L
GID4032R/L11-5	▲	▲	5.0	40	32	250	50	27	11		GB70-85-M6×14	WH50L
GID3225R/L08-6	▲	▲	6.0	32	25	200	40	20.5	8	G□MD6□□-□□	GB70-85-M5×12	WH40L
GID4032R/L11-6	▲	▲	6.0	40	32	250	50	27	11		GB70-85-M6×14	WH50L

▲ Stock available


△ Make-to-order

QC series shallow grooving tools code key

● External shallow grooving tools




● Internal shallow grooving tools







External shallow grooving tools



R-type shown. The right (R) holder is fitted with a right (R) insert, and the left (L) holder is fitted with a left (L) insert.



Type		Stock	Basic dimensions(mm)						Width (mm)	Applicable inserts	Screw	Wrench
			H	HF	B	WF	LH	LF				
GQCR/L	1616K16-15	▲	16	16	16	21	25.5	125	1.1-1.8	QC16R/L 110~180	I60M3.5×10	WT15IP
	2020K16-15	▲	20	20	20	25		125				
	2525M16-15	▲	25	25	25	30		150				
	1616K16-25	▲	16	16	16	21		125	1.8-3.0	QC16R/L 180~300		
	2020K16-25	▲	20	20	20	25		125				
	2525M16-25	▲	25	25	25	30		150				
	2020K22-15	▲	20	20	20	25		125	1.0-2.3	QC22R/L 100~230	I60M5×13	WT20IP
	2525M22-15	▲	25	25	25	30		150				
	2020K22-25	▲	20	20	20	25		125	2.3-3.3	QC22R/L 230~330		
	2525M22-25	▲	25	25	25	30		150				
	2020K22-35	▲	20	20	20	25		125	3.3-4.8	QC22R/L 330~480		
	2525M22-35	▲	25	25	25	30		150				



▲Stock available

△Make-to-order

Internal shallow grooving tools



L-type shown. The right (R) holder is fitted with a right (R) insert, and the left (L) holder is fitted with a left (L) insert.




Type	Stock	Basic dimensions(mm)					Width (mm)	Applicable inserts	Screw	Wrench
		DMIN	DCON	WF	LH	LF				
S20K-QC1115R/L 16	▲	16	20	11.1	40	125	1.2-1.8	QC11R/L 120~180	I60M2.5×6.5	WT07IP
S20K-QC1125R/L 16	▲	16	20	11.1	40	125	1.8-3.0	QC11R/L 180~300		
S16H-QC1115R/L 20	▲	21	16	11.5	12	100	1.2-1.8	QC11R/L 120~180		
S16H-QC1125R/L 20	▲	21	16	11.5	12	100	1.8-3.0	QC11R/L 180~300		
S20M-QC1615R/L 25	▲	26	20	12.5	15	150	1.1-1.8	QC16R/L 110~180	I60M3.5×10	WT15IP
S20M-QC1625R/L 25	▲			12.5			1.8-3.0	QC16R/L 180~300		
S25M-QC2215R/L 35	▲	35	25	18.2	20		1.0-2.3	QC22R/L 100~230	I60M5×13	WT20IP
S25M-QC2225R/L 35	▲			18.2	20		2.3-3.3	QC22R/L 230~330		
S25M-QC2235R/L 35	▲			18.2	20		3.3-4.8	QC22R/L 330~480		

▲Stock available

△Make-to-order


Parting and grooving tools code key

● External grooving






External parting and grooving tools: QZQ series



R-type shown



Type		Stock		Basic dimensions(mm)						Applicable inserts	Screw	Wrench	
		R	L	H	HF	B	LF	WF	CW	CDX _{max}			
QZQ	1616R/L03	▲	▲	16	16	16	100	16.4	3	16	ZQMX3N11-IE	GB70-85-M5×16	WH40L
	1616R/L04	▲	▲	16	16	16	100	16.4	4	18	ZQMX4N11-IE		
	2020R/L03	▲	▲	20	20	20	125	20.4	3	20	ZQMX3N11-IE	GB70-85-M6×20	WH50L
	2020R/L04	▲	▲	20	20	20	125	20.4	4	20	ZQMX4N11-IE		
	2525R/L03	▲	▲	25	25	25	150	25.4	3	20	ZQMX3N11-IE		
	2525R/L04	▲	▲	25	25	25	150	25.4	4	20	ZQMX4N11-IE		
	2525R/L05	▲	▲	25	25	25	150	25.4	5	25	ZQMX5N11-IE		
	2525R/L06	▲	▲	25	25	25	150	25.7	6	32	ZQMX6N11-IE		
	3225R/L03	▲	▲	32	32	25	170	25.4	3	25	ZQMX3N11-IE		
	3225R/L04	▲	▲	32	32	25	170	25.4	4	25	ZQMX4N11-IE		
	3225R/L05	▲	▲	32	32	25	170	25.4	5	25	ZQMX5N11-IE		
	3225R/L06	▲	▲	32	32	25	170	25.7	6	35	ZQMX6N11-IE		


▲ Stock available

△ Make-to-order

General
turningParting and
groovingSupplementary series parting
and grooving inserts

Center height control of parting and grooving tools

- No matter which parting or grooving tools you select, the ideal surface quality is only achieved by ensuring that insert is vertical from the center line of workpiece, which can also effectively reduce vibration during machining.
- The height tolerance between insert edge bottom and the center height of workpiece should be remained in $\pm 0.1\text{mm}$, especially for lever parting and grooving workpieces with small diameter. This can improve tool life, reduce cutting resistant force, and diminish burrs.




Parting

- When the insert is approaching the center of workpiece, the feed speed should be reduced by 30%, which is good for improving life and surface quality.
- As long as conditions allow, try to shorten the overhang of tools as much as possible to ensure good stability.


External grooving, turning and profiling

- In-feed sequence: When cutting depth $> 0.5\text{mm}$, radial in-feed (Max. cutting depth can be $0.75 \times \text{insert edge width } S$) $\rightarrow$ radial out-feed about 0.1mm $\rightarrow$ axial in-feed $\rightarrow$ flank out-feed $\rightarrow$ axial in-feed $\rightarrow$ radial machining to required depth.
- When finishing, adopt the sequence shown in the diagram. It can reduce vibration caused by the friction between tools and chips.




Surface grooving and turning

- Finishing (Multi-slot cutting)
Cut inwards from Max. diameter. Inserts offset to inward flange when retracting, as is shown in diagram (1).
- Recess turning
Axial turning depth should not exceed $0.75 \times S$ (cutting edge width).
If slot width is larger than slot depth, it is recommended to adopt recess turning, as is shown in diagram (2).
If slot depth is larger than slot depth, it is recommended to adopt multi-slot cutting.
- Finish machining
First finish bottom and external diameter fringe, then finish the internal diameter to required size, as is shown in diagram (3).



Internal grooving and turning

- To facilitate chip flow, always feed along the direction of moving from the deepest in the hole to outside.





Recommended cutting parameters for parting and grooving

Insert size	Recommended feed rate(mm/r)					
Insert width(mm)	Parting	Grooving	Grooving(-MM)	Turning	Turning(-MM)	Profiling
2.5	0.05-0.15	0.05-0.15	0.05-0.2	0.05-0.15	0.05-0.2	0.05-0.15
3	0.05-0.15	0.05-0.15	0.05-0.2	0.07-0.15	0.07-0.2	0.1-0.2
4	0.05-0.2	0.05-0.2	0.05-0.25	0.07-0.25	0.07-0.3	0.1-0.2
5	0.07-0.2	0.07-0.22	0.07-0.25	0.1-0.25	0.1-0.3	0.15-0.3
6	0.1-0.3	0.07-0.25	0.07-0.3	0.1-0.3	0.1-0.35	0.15-0.3
8			0.1-0.4		0.15-0.45	

Workpiece material	Hardness	YBG302	YBG202 YBG205	YBG105	YBG212	YBC151	YBC251	YBS103	YD101	YD201	YBG102	YC10	YC40
P Carbon steel	125 ≤ HB ≤ 170	120-260	150-280			140-280	150-280					130-280	110-260
Low alloy steel	180 ≤ HB ≤ 275	80-175	110-200			100-240	110-200					90-200	70-175
High alloy steel	180 ≤ HB ≤ 325	80-160	110-190			100-220	110-190					90-190	70-160
Cast steel	180 ≤ HB ≤ 250	75-140	100-170			80-160	100-170					80-170	60-140
M Ferrite, Martensite	200 ≤ HB ≤ 300	70-170	100-200				100-200					80-200	60-170
Austenite	180 ≤ HB ≤ 300	80-200	110-220				110-220					90-220	70-200
K Malleable cast iron	130 ≤ HB ≤ 230	100-200	130-220							90-160			
Grey cast iron	180 ≤ HB ≤ 220	90-170	120-200							80-140			
Nodular cast iron	160 ≤ HB ≤ 250	80-150	110-180							60-140			
N Al alloy	--								200-400				
S Super alloy	≤ 400			40-70	20-50			30-80	20-50		30-60		

The cutting parameters recommended are suitable for wet machining.

Advice: For internal machining and endface machining, the cutting speed should be reduced by 30%-40%.

Recommended cutting parameters for QC series shallow groove tools

Processed material	Recommended insert material (cutting speed m/min)		A: Tool feed for grooving(mm/r)				
	PVD Coating		B: Tool feed for horizontal processing(mm/r)				
	YBG202	YBG205	C: Depth of cut for horizontal processing(mm)				
			QC**R/L050-120	QC**R/L125-225	QC**R/L230-325	QC**R/L330-400	QC**R/L400-480
Carbon Steel	80-180	80-180	A: 0.03-0.08	A: 0.04-0.09	A: 0.05-0.1	A: 0.05-0.12	A: 0.05-0.12
			Non-horizontal processing	B: 0.04-0.09	B: 0.05-0.1	B: 0.05-0.1	B: 0.05-1
			Non-horizontal processing	C: 0.3(MAX)	C: 0.5(MAX)	C: 0.5(MAX)	C: 0.8(MAX)
Alloy Steel	80-160	80-160	A: 0.03-0.07	A: 0.04-0.08	A: 0.05-0.09	A: 0.05-0.1	A: 0.05-0.1
			Non-horizontal processing	B: 0.04-0.08	B: 0.05-0.09	B: 0.05-0.1	B: 0.05-1
			Non-horizontal processing	C: 0.3(MAX)	C: 0.5(MAX)	C: 0.5(MAX)	C: 0.5(MAX)
Stainless Steel	60-130	60-130	A: 0.03-0.07	A: 0.04-0.08	A: 0.05-0.09	A: 0.05-0.1	A: 0.05-0.1
			Non-horizontal processing	B: 0.04-0.08	B: 0.05-0.09	B: 0.05-0.1	B: 0.05-1
			Non-horizontal processing	C: 0.3(MAX)	C: 0.5(MAX)	C: 0.5(MAX)	C: 0.5(MAX)

The cutting parameters above are applicable to external grooving. When machining internal grooves, please reduce the cutting speed and feed by 10%.